



300 S. DAYTON ST. DAVISON, MI 48423 PH: 810-653-9626 FAX:810-654-2616

*This Part requires two clamps, part numbers 116-300 & 128-300. See additional drawings for information on these clamps.

Min/Max Temp.	-30/140 Degrees F	.X= F
Pressure Tested	4.3 PSI	
Material	Flexible PVC 60 Duro Shore A	A
Installation Torque	60" Lbs.	UNLESS O
Conforms to ASTM	D5926, C1173	
Box Quantity	20	INCHE
Clamps used	300 Series	,

3.36 lbs.

TOLERANCES: Coupling 6" AC/DI x 5" AC/DI Fractional ± $.XX = \pm .060$ $.XXX = \pm .032$ $ANG = \pm 0.5^{\circ}$ OTHERWISE SPECIFIED

DESCRIPTION:

1055-65 SCALE

DESIGNER: PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ES not to scale D. Brady FERNCO, INC. ANY REPRODUCTION IN 3RD ANGLE PROJECTION CHECKER: PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED. DATE: 3/19/2009 SHEET 1 OF 1 DO NOT SCALE DRAWING