


1056 Series - Cast Iron or Plastic to Cast Iron or Plastic



Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1056-125	1.63	41	1.63	41	3.45	88
1056-150/125	1.94	49	1.63	41	3.45	88
1056-150	1.94	49	1.94	49	3.43	87
1056-215	2.41	61	1.84	47	3.39	86
1056-222						
1056-22	2.41	61	2.41	61	3.45	88
1056-315	3.35	85	1.91	49	3.87	98
1056-350						
1056-32	3.52	89	2.38	60	3.96	101
1056-33	3.46	88	3.46	88	3.98	101
1056-415	4.4	112	1.91	49	3.96	101
1056-42	4.4	112	2.35	60	3.88	99
1056-43	4.46	113	3.52	89	4.03	102
1056-44	4.58	116	4.58	116	4.02	102
1056-44XL						
1056-53 *	5.56	141	3.53	90	3.9	99
1056-54	5.57	141	4.26	108	3.95	100
1056-55	5.52	140	5.52	140	3.97	101
1056-63 *	6.61	168	3.38	86	5.75	146
1056-64	6.61	168	4.46	113	5.75	146
1056-65	6.48	165	5.46	139	5.77	147
1056-66	6.6	168	6.6	168	5.74	146
1056-84 *	8.51	216	4.38	111	5.99	152
1056-86	8.51	216	6.38	162	5.99	152
1056-88	8.64	219	8.64	219	6.04	153
1056-10-6	10.25	260	6.38	162	6.23	158
1056-10-8	10.25	260	8.42	214	5.98	152
1056-1010	10.63	270	10.63	270	5.89	150
1056-1210	12.5	318	10.65	271	6.37	162
1056-1212	12.52	318	12.52	318	6.32	161
1056-1512	15.75	400	12.25	311	5.71	145
1056-1515	15.44	392	15.44	392	10	254
1056-1815 *	19	483	15.3	389	9.89	251
1056-1818	19	483	19	483	9.89	251
1056-2121	22.5	572	22.5	572	9.89	251
1056-2424	25.1	638	25.1	638	9.89	251
1056-2727	28.3	719	28.3	719	9.89	251

1056 Series - Condensate Pipe Connectors

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1056-075	1.05	27	1.05	27	2.38	60
1056-100	1.31	33	1.31	33	2.4	61

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent