


# 1002 Series - Clay to Cast Iron or Plastic



| Part No.      | Side A |        | Side B |        | Width C |        |
|---------------|--------|--------|--------|--------|---------|--------|
|               | inches | mm     | inches | mm     | inches  | mm     |
| 1002-43       | 5.25   | 133    | 3.38   | 86     | 3.91    | 99     |
| 1002-43WC     | 5.4    | 137.16 | 3.5    | 88.9   | 4       | 101.6  |
| 1002-44WC     | 5.4    | 137.16 | 4.56   | 115.82 | 4       | 101.6  |
| 1002-44WCRC   | 5.44   | 138.18 | 4.55   | 115.57 | 3.96    | 100.58 |
| 1002-46WCRC   | 5.5    | 139.7  | 6.6    | 167.64 | 5.74    | 145.8  |
| 1002-54WC     | 6.84   | 173.8  | 4.29   | 109.08 | 5.93    | 150.72 |
| 1002-55WC     | 6.81   | 172.91 | 5.17   | 131.32 | 5.81    | 147.59 |
| 1002-64WC     | 8      | 203.2  | 4.5    | 114.3  | 6       | 152.4  |
| 1002-64WCRC   | 8.02   | 203.71 | 4.57   | 116.08 | 6       | 152.4  |
| 1002-64WCRC-  | 8      | 203.2  | 4.38   | 111.25 | 6       | 152.4  |
| 1002-66WC     | 8      | 203.2  | 6.66   | 169.16 | 6       | 152.4  |
| 1002-66WCRC   | 8.04   | 204.1  | 6.38   | 162.14 | 5.91    | 150.01 |
| 1002-86WC     | 10     | 254    | 6.38   | 162.05 | 6       | 152.4  |
| 1002-88WC     | 10     | 254    | 8.66   | 219.96 | 6       | 152.4  |
| 1002-88WCRC   | 10     | 254    | 8.66   | 219.96 | 6       | 152.4  |
| 1002-1010WC   | 12.6   | 320.04 | 10.6   | 269.24 | 6.37    | 161.76 |
| 1002-1010WCRC | 12.4   | 314.96 | 10.6   | 269.24 | 5.9     | 149.86 |
| 1002-44       | 5.14   | 131    | 4.52   | 115    | 3.96    | 101    |
| 1002-46       | 5.18   | 132    | 6.39   | 162    | 5.82    | 148    |
| 1002-54       | 6.05   | 154    | 4.38   | 111    | 5.28    | 134    |
| 1002-64       | 7.34   | 186    | 4.29   | 109    | 5.56    | 141    |
| 1002-65       | 7.12   | 181    | 5.25   | 133    | 5.68    | 144    |
| 1002-66       | 7.35   | 187    | 6.61   | 168    | 5.76    | 146    |
| 1002-86       | 9.33   | 237    | 6.2    | 157    | 5.93    | 151    |
| 1002-88       | 9.63   | 245    | 8.43   | 214    | 5.74    | 146    |
| 1002-10-8     | 12.5   | 318    | 8.5    | 216    | 6.13    | 156    |
| 1002-1010     | 12.5   | 318    | 10.5   | 267    | 5.88    | 149    |
| 1002-1210     | 14.5   | 368    | 10.75  | 273    | 6.6     | 168    |
| 1002-1212     | 14.5   | 368    | 12.5   | 318    | 6.37    | 162    |
| 1002-1212WC   | 16.29  | 413.64 | 12.39  | 314.6  | 6.3     | 160.1  |
| 1002-1212WCRC | 15.25  | 387.35 | 12.6   | 320.04 | 6.42    | 163.07 |
| 1002-1512     | 18.14  | 461    | 12.6   | 320    | 6.85    | 174    |
| 1002-1515     | 18.14  | 461    | 15.6   | 396    | 6.85    | 174    |
| 1002-1515WC   | 19.82  | 503.43 | 15.43  | 391.92 | 9.68    | 245.95 |
| 1002-1818 *   | 21.9   | 556    | 18.88  | 480    | 9.63    | 245    |
| 1002-1818WC   | 22.59  | 573.79 | 18.9   | 480.06 | 9.89    | 251.29 |
| 1002-2121 *   | 25.4   | 645    | 22.3   | 566    | 10.14   | 258    |
| 1002-2424 *   | 28.97  | 736    | 25     | 635    | 10.14   | 258    |
| 1002-2727 *   | 32.4   | 823    | 28.2   | 716    | 10.14   | 258    |

\* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent