



1006 Series - Concrete to Cast Iron or Plastic						
Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1006-43	5.56	141	3.53	90	3.9	99
1006-44	5.57	141	4.31	109	3.96	101
1006-64	7.75	197	4.31	109	5.92	150
1006-65 *	7.66	195	5.5	140	5.86	149
1006-66	7.66	195	6.65	169	5.86	149
1006-84	10.25	260	4.38	111	6.18	157
1006-86 *	10.25	260	6.38	162	6.18	157
1006-88	10.25	260	8.5	216	5.93	151
1006-12-6						
1006-10-8 *	12.5	318	8.38	213	6.62	168
1006-10-8RC	12.4	314.96	8.38	212.85	5.9	149.86
1006-1010	12.6	320	10.6	269	6.37	162
1006-12-8	16.29	414	8.38	213	6.55	166
1006-1210 *	16.29	414	10.75	273	6.55	166
1006-1210RC	15.25	387.35	10.6	269.24	6.42	163.07
1006-1212	16.29	414	12.39	315	6.3	160
1006-1515 *	19.82	503	15.43	392	9.68	246
1006-1818 *	22.5	572	18.9	480	9.89	251
1006-2121 *	26.7	678	22.3	566	9.89	251
1006-2424 *	30.5	775	25	635	9.89	251
1006-2727 *	34	864	28	711	9.89	251

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent