



1051 Series - Asbestos Cement Fibre or Ductile Iron to Cast Iron or Plastic

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1051-43	4.8	122	3.38	86	4.06	103
1051-44	4.8	122	4.4	112	4.06	103
1051-45	5	127	5.52	140	4.22	107
1051-53						
1051-54	5.75	146	4.47	114	3.95	100
1051-55	6.05	154	5.54	141	5.03	128
1051-64	6.84	174	4.3	109	5.93	151
1051-65	6.81	173	5.17	131	5.81	148
1051-66	7.66	195	6.39	162	5.85	148
1051-86 *	9.12	232	6.38	162	6.23	158
1051-88	9.12	232	8.49	216	5.98	152
1051-10-8 *	11.05	281	8.38	213	5.95	151
1051-1010	11.05	281	10.65	271	5.95	151
1051-1210 *	13	330	10.75	273	6.49	165
1051-1212	13	330	12.38	314	6.24	158
1051-1215	15.44	392	13.2	335	10	254
1051-1515	15.9	404	15.9	404	9.89	251
1051-1615	18.14	461	15.6	396	6.85	174
1051-1818	19.7	500	18.9	480	9.89	251

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent