

Connecting 1002 Series - Clay to Cast Iron or Plastic

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1002-43RC*	5.29	134.37	3.38	85.85	4.1	104.14
1002-44RC	5.36	136.14	4.51	114.55	4.07	103.38
1002-44WCRC	5.44	138.18	4.55	115.57	3.96	100.58
1002-46RC*	6.6	167.64	5.13	130.18	5.74	145.8
1002-55RC*	6.6	167.64	5.5	139.7	5.74	145.8
1002-64RC*	7.5	190.5	4.5	114.3	6.02	152.91
1002-64WCRC	7.84	199.14	4.5	114.3	5.955	151.26
1002-64WCRC-SDR	7.84	199.14	4.38	111.25	5.955	151.26
1002-66RC	7.5	190.5	6.56	166.65	5.89	149.68
1002-66WCRC	7.84	199.14	6.52	165.61	5.955	151.26
1002-86RC*	9.65	245.11	6.63	168.4	5.99	152.15
1002-88RC	9.76	247.95	8.57	217.63	5.96	151.38
1002-88WCRC	10	254	8.49	215.65	5.92	150.37
1002-10-8RC*	12.4	314.96	8.5	215.9	5.9	149.86
1002-1010RC*	12.4	314.96	10.75	273.05	5.9	149.86
1002-1010WCRC	12.4	314.96	10.75	273.05	5.9	149.86
1002-1210RC*	14.51	368.55	12.6	320.04	6.38	162.05
1002-1212RC*	14.51	368.55	12.6	320.04	6.38	162.05
1002-1212WCRC	15.25	387.35	12.6	320.04	6.42	163.07
1002-1215RC*	15.25	387.35	14.38	365.25	6.42	163.07
1002-1515RC*	18.14	461.76	15.4	391.16	9.89	251.27
1002-1818RC*	21.9	556.26	19	482.6	9.63	244.6
1002-2121RC*	25.46	646.68	22.3	566.42	9.89	251.21
1002-2424RC*	28.97	735.84	25	635	9.89	251.21

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent