

Connecting 1051 Series - Asbestos Cement Fibre (AC) or Ductile Iron to Cast Iron or Plastic

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1051-44RC	4.8	121.92	4.39	111.51	3.94	100.08
1051-45RC*	5	127	5.5.52	140.21	3.97	100.84
1051-46RC*	4.75	120.65	6.6	167.64	5.74	145.8
1051-55RC*	5.9	149.86	5.5	139.7	5.92	150.37
1051-64RC*	6.95	176.53	4.38	111.25	5.92	150.37
1051-65RC*	6.95	176.53	5.5	139.7	5.92	150.37
1051-66RC	6.96	176.78	6.69	169.8	5.91	150.11
1051-86RC*	9.05	229.87	6.38	162.05	5.89	149.61
1051-8-10RC*	10.63	270	9.05	229.87	5.89	149.61
1051-88RC	9.25	234.95	8.51	216.15	5.97	151.51
1051-10-8RC*	11.02	279.91	8.38	212.85	5.97	151.51
1051-1210RC*	13.3	337.82	10.6	269.24	5.97	151.51
1051-1212RC*	13.37	339.6	12.6	320.04	5.97	151.51
1051-1818RC	19.74	501.27	19.74	501.4	9.89	251.28

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent