

Connecting 1056 Series - CI, PL, Copper, ST or Lead to CI, PL, Copper, ST or Lead

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1056-150RC	1.94	49.28	1.94	49.28	3.43	87.12
1056-22RC	2.41	61.21	2.41	61.21	3.45	87.63
1056-32RC*	3.52	89.41	2.38	60.45	3.96	100.58
1056-33RC	3.46	87.88	3.46	87.88	3.98	101.09
1056-43RC*	4.58	116.33	3.38	85.85	4.02	102.11
1056-44RC	4.58	116.33	4.58	116.33	4.02	102.11
1056-54RC*	5.52	140.21	4.38	111.25	3.97	100.84
1056-55RC	5.52	140.21	5.52	140.21	3.97	100.84
1056-64RC*	6.6	167.64	4.5	114.3	5.74	145.8
1056-65RC*	6.6	167.64	5.62	142.75	5.74	145.8
1056-66RC	6.6	167.64	6.6	167.64	5.74	145.8
1056-86RC*	8.64	219.46	6.38	162.05	6.04	153.42
1056-88RC	8.64	219.46	8.64	219.46	6.04	153.42
1056-1010RC	10.63	270	10.63	270	5.89	149.61
1056-1212RC	12.52	318.01	12.52	318.01	6.32	160.53
1056-1515RC	15.92	404.37	15.92	404.37	9.89	251.21
1056-1818RC	19.1	485.14	19.1	485.14	9.89	251.21

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent