

Connecting 5001RC Series - Clay to Clay

| Part No.      | Side A |        | Side B |        | Width C |        |
|---------------|--------|--------|--------|--------|---------|--------|
|               | inches | mm     | inches | mm     | inches  | mm     |
| 5001-44RC     | 5.29   | 134.37 | 5.29   | 134.37 | 4.1     | 104.14 |
| 5001-44WCRC   | 5.51   | 139.95 | 5.51   | 139.95 | 3.97    | 100.84 |
| 5001-66RC     | 7.5    | 190.5  | 7.5    | 190.5  | 6.02    | 152.91 |
| 5001-66WCRC   | 8.01   | 203.45 | 8.01   | 203.45 | 6       | 152.4  |
| 5001-88RC     | 9.65   | 245.11 | 9.65   | 245.11 | 5.99    | 152.15 |
| 5001-88WCRC   | 10     | 254    | 10     | 254    | 6       | 152.4  |
| 5001-1010RC   | 12.4   | 314.96 | 12.4   | 314.96 | 5.9     | 149.86 |
| 5001-1010WCRC | 12.4   | 314.96 | 12.4   | 314.96 | 5.9     | 149.86 |

\* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent