

Connecting 5002RC Series - Clay to Cast Iron or Plastic

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
5002-44RC	5.36	136.14	4.51	114.55	4.07	103.38
5002-44WCRC	5.44	138.18	4.55	115.57	3.96	100.58
5002-64RC *	7.5	190.5	4.5	114.3	6.02	152.91
5002-64WCRC *	8	203.2	4.5	114.3	6	152.4
5002-66RC	7.5	190.5	6.56	166.65	5.89	149.68
5002-66WCRC	8.04	204.1	6.38	162.14	5.91	150.01
5002-88RC	9.76	247.95	8.57	217.63	5.96	151.38
5002-88WCRC	10	254	8.66	219.96	6	152.4
5002-1010RC *	12.4	314.96	10.75	273.05	5.9	149.86
5002-1212RC *	14.51	368.55	12.6	320.04	6.38	162.05
5002-1515RC *	18.14	460.76	15.4	391.16	9.89	251.21
5002-1818RC *	21.9	556.26	19	482.6	9.63	244.6

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent