

Connecting 1001 Series - Clay to Clay

Part No.	Side A		Side B		Width C	
	inches	mm	inches	mm	inches	mm
1001-44RC	5.29	134.37	5.29	134.37	4.1	104.14
1001-44WCRC	5.51	139.95	5.51	139.95	3.97	100.84
1001-64RC*	7.5	190.5	5.5	139.7	6.02	152.91
1001-66RC	7.5	190.5	7.5	190.5	6.02	152.91
1001-66WCRC	7.87	199.9	7.87	199.9	5.925	150.5
1001-88RC	9.65	245.11	9.65	245.11	5.99	152.15
1001-88WCRC	10	254	10	254	5.945	151
1001-1010RC	12.4	314.96	12.4	314.96	5.9	149.86
1001-1010WCRC	12.4	314.96	12.4	314.96	5.9	149.86
1001-1212RC	14.51	368.55	14.51	368.55	6.38	162.05
1001-1212WCRC	15.25	387.35	15.25	387.35	6.42	163.07
1001-1515RC	18.14	460.76	18.14	460.76	9.89	251.21
1001-1818RC	21.9	556.26	21.9	556.26	9.63	244.6
1001-2424RC	28.97	735.84	28.97	735.84	9.89	251.21

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent