

® 4700 W. 160th St. Cleveland, 0H 44135 PH:800-321-9532 FX:800-321-9535 www.oatey.com

RAIN COLLAR FOR NO-CALK ROOF FLASHING



TECHNICAL SPECIFICATION

Engineering Specification: Oatey Rain Collar for No-Calk Roof Flashings can be used as a secondary seal for commercial and residential applications where a watertight seal for roof penetrations around the plumbing vent pipe is required.

Job Reference



- Non-fading sealing collar
- Not for hot-mopped or built-up roofs
- Do not use paint or petroleum based products on rubber collars
- Slides over existing roof flashing

√	Product No.	Description	PACK	CARTON WEIGHT
	14122	1-1/4" - 1-1/2" Rain Collar for No-Calk Roof Flashing	36	2 lbs.
	14135	2" Rain Collar for No-Calk Roof Flashing	24	2 lbs.
	14193	3" Rain Collar for No-Calk Roof Flashing	24	3 lbs.
	14203	4" Rain Collar for No-Calk Roof Flashing	12	5 lbs.
	14136	1-1/2 "- 3" Rain Collar for No-Calk Roof Flashing	24	3 lbs.
	14137	3"- 4" Rain Collar for No-Calk Roof Flashing	24	10 lbs.