



4700 W. 160th St.
Cleveland, OH 44135
PH: 800-321-9532
FX: 800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

BRASS SHOWER DRAIN



TECHNICAL SPECIFICATION: Oatey Brass Shower Drains are designed for use with preformed shower stall bases. The drain body is sealed to the shower base with a rubber gasket and fiber slip washer. Three DWV connection methods provide a drain for all applications of metallic pipe. Drain top accommodates 4- $\frac{1}{4}$ " Universal Snap-Tite Strainers available in a variety of designer finishes.



1 1/2" NPT Connection



2" NPT Connection



2" Caulking Connection




PHYSICAL/CHEMICAL PROPERTIES

Material

Cast Brass

COMMON APPLICATIONS

Oatey Brass Shower Drains are designed for use with preformed shower stall bases. The drain body is sealed to the shower base with a rubber gasket and fiber slip washer. Three DWV connection methods provide a drain for all applications of metallic pipe. Drain top accommodates 4- $\frac{1}{4}$ " Universal Snap-Tite Strainers available in a variety of designer finishes.

	PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
	42050	2" Brass Caulk Shower Drain w/Stainless Steel Strainer (101 BR)	6	10 lbs.
	42070	1- $\frac{1}{2}$ " NPT IPS Brass Caulk Shower Drain w/Stainless Steel Strainer (101 NPT)	6	9 lbs.
	42073	2" NPT IPS Brass Caulk Shower Drain w/Stainless Steel Strainer (101 NPT)	6	10 lbs.