# MATERIAL SAFETY DATA SHEET **MULTI PURPOSE LITHIUM GREASE**

5 pages

11300,11301,11302,11306 11315,11316,11328,11330 11332.

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME:

MULTI PURPOSE LITHIUM GREASE

PART No.:

MC 2215PB

UN/NA (PIN) No.:

N/A

**APPLICATIONS:** 

Lubricating Grease

**EMERGENCY TELEPHONE:** 

Info Trac - (800) 535-5053

SUPPLIER:

Chemtool Incorporated 8200 Ridgefield Road

P.O. Box 538

Crystal Lake, IL 60039-0538

TELEPHONE: FAX:

(815) 459-1250 (815) 459-1955

# 2. COMPOSITION, INFORMATION ON INGREDIENTS

INGREDIENT NAME:

CAS No .:

**CONTENTS:** 

**EPA RQ:** 

TPQ:

PETROLEUM DISTILLATES AND RESIDUAL

70-100 %

N/A

N/A

OILS\*\*

CARBON BLACK

1333-86-4

0.1-1 %

N/A

N/A

#### **COMPOSITION COMMENTS:**

Refer to section eight for exposure limits on ingredients.

Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

\*\*Mixture of CAS Registry Numbers 64742-52-5 and 64742-57-0.

# 3. HAZARDS IDENTIFICATION

Exposure to vapors generated at high temperatures, may cause respiratory irritation.

## **CHRONIC EFFECTS:**

**SENSITIZATION:** 

No known information.

#### CARCINOGENICITY:

Product contains:

IARC-3 and NIOSH-X listed carcinogen(s): Carbon Black, CAS # 1333-86-4, 0.1 - 1%

#### **HEALTH WARNINGS:**

INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product. SKIN CONTACT. Repeated or prolonged contact can result in drying of the skin. EYE CONTACT. Irritating, INGESTION. Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

#### ROUTE OF ENTRY:

Inhalation. Skin and/or eye contact. Ingestion.

#### **MEDICAL SYMPTOMS:**

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not determined

#### 4. FIRST AID MEASURES

INHALATION:

Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product,

immediately remove from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties

oxygen may be necessary. Get medical attention if any discomfort continues.

INGESTION:

DO NOT INDUCE VOMITING! Get medical attention immediately!

SKIN:

Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort

continues.

EYES:

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Contact physician if discomfort

continues.

# 5. FIRE FIGHTING MEASURES

FLASH POINT (°F):

435

FLAMMABILITY LIMIT - LOWER(%):

N/D

FLAMMABILITY LIMIT - UPPER(%):

N/D

#### **EXTINGUISHING MEDIA:**

Use: Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist.

## SPECIAL FIRE FIGHTING PROCEDURES:

Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

METHOD: Cd OC (Cleveland open cup).

1

1000 \*\*\*

#### **UNUSUAL FIRE & EXPLOSION HAZARDS:**

Pressure will increase in over heated, closed containers.

## **HAZARDOUS COMBUSTION PRODUCTS:**

Acrid smoke/fumes. Oxides of: Carbon.

## PROTECTIVE MEASURES IN CASE OF FIRE:

Self-contained breathing equipment and chemical resistant clothing recommended.

#### 6. ACCIDENTAL RELEASE MEASURES

#### **PERSONAL PRECAUTIONS:**

Minimize skin contact.

## PRECAUTIONS TO PROTECT THE ENVIRONMENT:

Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.

#### SPILL CLEAN-UP PROCEDURES:

Keep all sources of ignition and hot metal surfaces away from spill. Avoid contact with eyes or skin. Place leaking containers in well ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use absorbant material. Avoid discharge to natural water ways.

# 7. HANDLING AND STORAGE

# HANDLING PRECAUTIONS:

Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. Avoid spilling, skin and eye contact. Eye wash and emergency shower must be available at the work

#### STORAGE PRECAUTIONS:

Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.

#### STORAGE CRITERIA:

Chemical storage.

# 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

INGREDIENT NAME: PETROLEUM DISTILLATES AND RESIDUAL OILS**	CAS No.:	OSHA TWA:	PEL: STEL: NAV	ACGIH TWA: 5	STEL:	OTHER TWA: NAV	STEL	UNITS: mg/m3
CARBON BLACK	1333-86-4	3.5	N.E.	3.5	N.E.	3.5	N.E.	mg/m3

#### PROTECTIVE EQUIPMENT:





#### **ENGINEERING CONTROLS:**

Use engineering controls to reduce air contamination to permissible exposure level.

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds VENTILATION: acceptable level.

RESPIRATORS: No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

#### PROTECTIVE GLOVES:

Chemical resistant gloves recommended to prevent prolonged or repeated contact.

#### **EYE PROTECTION:**

Wear splash-proof eye goggles to prevent any possibility of eye contact.

## PROTECTIVE CLOTHING:

Wear appropriate clothing to prevent repeated or prolonged skin contact.

# **HYGIENIC WORK PRACTICES:**

Wash at the end of each work shift and before eating, smoking and using the toilet.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE:

Grease.

< 0.1

0.90

COLOR:

Black.

ODOR:

Mild (or faint). Petroleum.

SOLUBILITY DESCRIPTION:

Insoluble in water.

SOLUBILITY VALUE (g/100g H2O 68°F):

DENSITY/SPECIFIC GRAVITY (g/ml):

TEMPERATURE (°F): 61

#### 12271 - MULTI PURPOSE LITHIUM GREASE

VAPOR DENSITY (air=1):

>5

VAPOR PRESSURE:

<0.01 mmHg

TEMPERATURE (°F): 68

REFERENCE:BuAc=1

**EVAPORATION RATE:** 

<1

pH-VALUE, CONC. SOLUTION:

N/A

## 10. STABILITY AND REACTIVITY

STABILITY:

Normally stable.

CONDITIONS TO AVOID:

Avoid contact with acids and oxidizing substances.

HAZARDOUS POLYMERIZATION:

Will not occur.

POLYMERIZATION DESCRIPTION:

Not applicable

**HAZARDOUS DECOMPOSITION PRODUCTS:** 

Oxides of: Carbon.

# 11. TOXICOLOGICAL INFORMATION

## TOXICOLOGICAL INFORMATION:

No experimental toxilogical data on the preparation as such is available.

#### 12. ECOLOGICAL INFORMATION

#### **ECOLOGICAL INFORMATION:**

There is no ecological data on the product itself.

## 13. DISPOSAL CONSIDERATIONS

#### **DISPOSAL METHODS:**

Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

# 14. TRANSPORT INFORMATION

PRODUCT RQ:

N/A

U.S. DOT:

**UN/NA No.:** 

N/A

U.S. DOT HAZARD LABEL:

No DOT label requirement noted

U.S. DOT CLASS:

Not regulated.

**SEA TRANSPORT:** 

INFORMATION ON SEA TRANSPORT:

Not regulated

AIR TRANSPORT:

INFORMATION ON AIR TRANSPORT:

Not regulated

# 15. REGULATORY INFORMATION

**REGULATORY STATUS OF INGREDIENTS:** 

NAME:

PETROLEUM DISTILLATES AND

RESIDUAL OILS\*\*
CARBON BLACK

CAS No:

TSCA: CERCLA: SARA 302:

N/A

N/A

**SARA 313:** 

DSL(CAN):

N/A Yes

1333-86-4

Yes

Yes

N/A

N/A

Yes

US FEDERAL REGULATIONS: REGULATORY STATUS:

This Product or its components, if a mixture, is subject to following regulations (Not meant to be all inclusive - selected regulations represented): TSCA: The ingredients of this product are on the TSCA Inventory. SARA 311 Categories: NONE. Section 313: This product may contain foxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372 Zinc compounds up to 3% and Antimony compounds up to 0.5%.

CANADIAN REGULATIONS: LABELS FOR SUPPLY:

**REGULATORY STATUS:** 

This Material Safety Data Sheet has been prepared in compilance with the Controled Product Regulations.

# 16. OTHER INFORMATION

NFPA HAZARD RATING:

**HEALTH:** 

FLAMMABILITY: REACTIVITY:

SPECIAL HAZARD:

.

Burns only if pre-heated (1). N/A (0).

N/A

NPCA HMIS HEALTH: PERS. PROTECT. INDEX:

1 Slight Hazard

Irritation, minor residual injury (1)

В

PREPARED BY:

Heather Holich

DATE:

March 15, 2002

#### DISCLAIMER:

While the information and recommendations set forth herein are believed to be accurate as of the date thereof, Chemtool Incorporated makes no warranty with respect thereto and disclaims all liability from reliance therein.