

# Venture 1599B *UL181B-FX Listed* Flexible Duct Closure Tape



- *HALF THE COST* of cloth duct tape
- *UL181B-FX Listed: Meets all Texas building codes*
- *Higher adhesion and tack than traditional cloth duct tapes*
- *Can be used on metal & metal connections*
- *Excellent UV resistance*
- *Long-life CW<sup>®</sup> acrylic adhesive; superior performance in extreme environments; from -35°F to 260°F*
- *2 inch x 120 yard rolls*



Venture Tape Corp.  
30 Commerce Rd., Rockland, MA 02370  
Tel 781 331-5900; Fax 781 871-0065

**800-343-1076**  
[www.venturetape.com](http://www.venturetape.com)

**VentureTape<sup>®</sup>**

# 1599B

## UL-181B-FX Printed 3 Mil Flexible Duct Closure Tape

### Description

A polypropylene film with an acrylic CW® cold weather adhesive system. This adhesive will perform well in either sub-zero cold or abnormally warm temperatures, including hot attics. Listed with Underwriters Laboratories and meets all requirements of UL 181B-FX as they relate to closure systems for use with flexible air ducts and air connectors.

**This product can only be used on metal and metal connections.**

### Applications:

Primarily used for sealing flexible air ducts and air connectors.

## Technical Data

	Imperial	Metric
Thickness	2.5 mils	0.0508 mm
Adhesion		
Peel - To Stainless Steel	41 oz/in width	11.4 N/2.5 cm
- To Backing:	31 oz/in width	8.6 N/2.5 cm
Shear: Indefinite @	2.2 psi	15.2 kPa
Hot Shear: 150°F Indefinite @	2.2 psi	15.2 kPa
Tensile	22 lb/inch	99.4 N/2.5 cm
Elongation	150%	150%
Temperature Range	-35° F to 260° F	-37° C to 127° C
Mold Growth	0	0
Roll Size	2" x 120 Yards	5.1 cm x 110 m

### Important Information:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Users must determine the product suitability for the end use application and assume all risks and liabilities.