



DATE 02-12-99

EMERGENCY TELEPHONE NUMBER  
(605) 232-4311

**PRODUCT IDENTIFICATION:**

**Material No.:** 1005 & 16923

**Material Name:** Thum-Gum Caulking Cords

**Material Description:** White pliable strands

**WARNING STATEMENT:**

Prolonged exposure may cause dermatitis.

**PRECAUTIONARY MEASURES:**

Normal chemical hygiene should be adequate to handle this material.  
Wash thoroughly after handling, avoid contact with eyes, do not ingest.

**HAZARDOUS INGREDIENTS:**

<u>Material Name/CAS #</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
----------------------------	----------	-----------------	------------------

This MSDS is prepared to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Unlisted Ingredients are not "hazardous" per this OSHA standard and are considered to be trade secrets.

**EMERGENCY AND FIRST AID PROCEDURES:**

**FIRST AID:**

**Ingestion:** Seek medical attention if large amounts are ingested.

**Skin:** Wash with soap and water. Launder contaminated cloths before reuse.

**Eyes:** Flush with water for 15 minutes, consult physician.

**OTHER EMERGENCIES:**

**In case of fire:** Extinguish with water CO<sub>2</sub>, foam or dry chemical.

**Spill or leak:** Material poses no special threat if spilled or leaked.

**OCCUPATIONAL CONTROL PROCEDURES:**

**Eye Protection:** Not normally required; although the use of safety glasses is a good industrial practice.

**Skin Protection:** Wear protective gloves for prolonged exposures.

**Respiratory Protection:** Not normally required.

**Ventilation:** Not normally required.

**FIRE PROTECTION:**

**Flash point/method:** Not determined

**Appropriate Extinguishers:** Water, CO<sub>2</sub>, foam or dry chemical

**Special Fire Fighting Procedures:** Wear self-contained breathing apparatus when fighting fire.

**Unusual Fire and Explosion Hazard:** None known

**REACTIVITY DATA:**

**Stability:** Stable

**Incompatibility:** Strong oxidizers

**Hazardous Decomposition Products:** Carbon oxides and unidentified organic compounds when burning.

**Hazardous polymerization:** Will not occur

**EFFECT OF OVER EXPOSURE:**

**Eyes:** Mechanical irritation

**Skin:** May cause mild irritation. Prolonged exposure may cause dermatitis

**Inhalation:** Not applicable

**Chronic:** No known effects

**Existing Health Conditions Affected by Exposure:** No known conditions are aggravated by exposure to this product.

**CARCINOGENICITY:**

**NTP?**  
No

**IARC?**  
No

**OSHA?**  
No

**PHYSICAL DATA:**

**Physical State:** Solid

**Specific Gravity:** 1.6 @ 77°F

**SPILL, LEAK & DISPOSAL INFORMATION:**

**Spill or Leak Procedure:** Sweep or scrape up and place in appropriate container for disposal.

**Waste Disposal:** Observe all Federal, State and Local regulations when disposing of the material. For assistance contact the District Director of the Environmental Protection Agency, local hazardous waste regulations may apply if they are different from the federal regulations. Dispose of in an approved industrial landfill.

**Storage:** No special requirements for storage.

**EPA INFORMATION:**

**SARA Title III sections 313 and 302:** Contains no listed materials

**CERCLA:** Contains no listed materials

**DOT Shipping Name:** Caulking compound NOIBN

The above information is based on MSDS's provided by the suppliers of the raw materials used in this product.