ACTS[®] axed AST!

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # Hercules Jel Flux



1.0mg/m³ (fumes) N/A

1.0mg/m³ (fumes) N/A

MATERIAL SAFETY NFORMATION SERVICE

26%

- -

Date Prepared: 2/21/1990 Last Reviewe	111 South Street Passaic N L 07055			
Meets OSHA 29 CFR 1910.1200				
Section 2 - Hazardous Ingredients/Identity Ir	nformation			
Hazardous Components (Specific Chemical Identity; Common Name(s), CAS Numbers)	OSHA PEL	ACGIH TLV	Other Limits	Upper Bound Limit if SARA Reportable

1.0mg/m³

N/A

6

Zinc Chloride (7646-85-7) Ammonium Chloride (12125-02-9)

HMIS Hazard Rating: Health: 2 Flammability: 0 Reactivity: 1 Personal Protection: C

Section 3 - Physical/	Chemical Characteristic	s			
Boiling Point (°F):		Specific Gravity (H2O = 1):	Vapor Density (Air = 1):	Vapor P (mm	
212		1.25	>1	At 100	° C 76
Melting Point (° F):	Evaporation Rate: (Butyl Acetate = 1)	Solubility in Water:			
N/A	<1	100% miscible in wate	r	VOC Level (g/l):	0
Appearance And Color:	Greenish yellow cold	or	Odor: None		
Section 4 - Fire And	Explosion Hazard Data	1			
Flash Point:			Flammable Limits:	LEL:	UEL:
None			N/A		

Extinguishing Media: As appropriate for surrounding fire.

Special Firefighting Procedures:

None

Unusual Fire And Explosion Hazards:

None

Continued on Next Page

Section 5 - Reactiv	vity Data			
Stability: Stable	Conditions To Avoid:	Avoid contact with concentrated alkalis.		
Incompatability (Materials To Avoid):	Zinc chloride is incompatible with cyanides (may release toxic HCN gas) & sulfide salts (may release toxic H2S gas)			
Hazardous Decomposit	ion: Will not occur	except at high temperatures		
Hazardous Polymerizat	ion: Will not occur			
Section 6 - Health	Hazard Data			
Routes of Entry: In	halation N/A	Skin YES/Primary Ingestion YES/Primary		

Health Hazards:

Individuals with pre-existing diseases of lungs may have increased susceptibility to the toxicity of excessive exposures to zinc chloride.

Carcinogenicity: NTP NO IARC NO OSHA Regulated NO

Signs And Symptoms of Exposure:

INGESTION: Severe damage to internal organs (esophagus & pylorus) will occur if swallowed in large quantities. SKIN CONTACT: Prolonged contact causes burns, skin irritation with discomfort and rash. EYE CONTACT: Will cause eye irritation with discomfort, tearing or blurring of vision.

Medical Conditions Generally Aggravated By Exposure:

Emergency And First Aid Procedures:

INGESTION: Do not induce vomiting. If conscious, dilute by giving large quantities of water or milk. Call a physician immediately. SKIN CONTACT: Wash affected skin area with soapy water. Remove contaminated clothing. If burn or rash appears consult a physician. EYE CONTACT: Immediately flush eyes with plenty of water for 15 minutes. Consult a physician.

Continued on Next Page

Section 7 - Preca	utions For Safe Handling And Use:		
Steps To Be Taken In (Case Material Is Released Or Spilled:		
Flush with large qu Waste Disposal Metho	antities of water and pick up with absorb d:	bing materials.	
Landfill, to dispose	of large quantities, comply with federal,	, state and local reg	gulations.
Precautions To Be Tak	en In Handling And Storing:		
If handling in large	quantities, wear rubber gloves & goggle	es.	
Other Precautions:			
None			
Section 8 - Contro	ol Measures:		
Respiratory Protection	1:		
	or other circumstances where adequate pressure airline mask, or self contained		
Ventilation: Local Ex	khaust N/A	Special	N/A
Mechani	ical Exhaust fan		
Gloves:	Rubber gloves	Other:	Ν/Δ
Eye Protection:	Safety goggles	Other:	N/A
Other Protective Clothing:	Gloves while handling the material.		
Work/Hygienic Practice	es: Wash thoroughly after handling.		
	vvasn thoroughly after handling.		



MATERIAL

SAFETY

INFORMATION

SERVICE



For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.