MATERIAL SAFETY INFORMATION SERVICE


Material Safety Data Sheet # 303

Hercules Chemical Company Inc. 111 South Street

Passaic NJ 07055-7398

Information Telephone: 1-800 221-9330

Internet: www.herchem.com



Preparation 4/21/06 Revision Date 6/14/11 Revision Number 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identity: Liquid Glug – Bathroom Intended Use: Unclogging bathroom drains

Manufacturer: Hercules Chemical Company, Inc.

111 South Street

Passaic, New Jersey 07055-7398

Internet: http://www.herchem.com

Information Telephone: (800) 221-9330

Emergency Phone: CHEMTREC: (800) 424-9300

MSDS Date of Preparation: 04/21/06

2. HAZARDS IDENTIFICATION

This product is a clear, colorless liquid with chlorine odor.

Emergency Overview

May cause severe eye and skin irritation or damage with possible burns.
Inhalation of vapors or mists may cause
mucous membrane and respiratory irritation. Harmful if swallowed.

Ingestion: Ingestion may cause severe irritation or burns to the mucous membranes, esophagus and stomach. **Inhalation:** Inhalation of vapors or mists may cause irritation of the nose throat and upper respiratory tract. **Eye:** Liquid or mists may cause severe irritation or burns with redness, tearing and stinging of the eyes. May cause eye damage.

Skin: Liquid or mists may cause severe irritation with possible burns on prolonged contact

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount
Sodium Hypochlorite	7681-52-9	40-60%
Potassium Hydroxide	1310-58-3	1-5%
Sodium Silicate	1344-09-8	1-5%
Water	7732-18-5	30-50%

4. FIRST AID MEASURES

Eye: Immediately flush victim's eyes with large quantities of water for at least 15 minutes, holding the eyelids apart. Remove contact lenses if present. Get immediate medical attention.

Skin: Immediately flush skin with plenty of water for 15 minutes while removing contaminated clothing and shoes.

Ingestion: DO NOT INDUCE VOMITING. If conscious, rinse mouth thoroughly with cold water. Never give anything by mouth to an unconscious or convulsing person Get immediate medical attention.

Inhalation: Immediately remove victim to fresh air. If breathing is difficult have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get immediate medical attention.

Other: Not applicable

5. FIRE FIGHTING MEASURES

Flash Point: None

Auto ignition Temperature: Not applicable

Flammable Limits: LEL: Not applicable UEL: Not applicable

Extinguishing Media: Use media appropriate for surrounding fire. Cool fire exposed containers and structures

with water.

Unusual Fire or Explosion Hazards: Reacts with most metals to form flammable hydrogen gas.

Special Fire-Fighting Instructions: Firefighters should wear positive pressure self-contained breathing

apparatus and full protective clothing.

Hazardous Combustion Products: None.

Explosion Data: (sensitivity to mechanical impact or static discharge): None known.

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate protective clothing as described in Section 8. For small spill, flush with large amount of water. For larger spill, contain liquid and neutralize with dilute acid such as acetic or hydrochloric. Flush neutralized spill to sewer if permitted or collect using an inert absorbent material and place in appropriate containers for disposal. Prevent spill from entering sewers and water courses. Report releases as required by local, provincial

7. HANDLING AND STORAGE

Handling: Prevent contact with the eyes, skin and clothing. Avoid breathing mists. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Do not mix with other drain cleaners. Dangerous chemical reactions, boiling or splattering may occur.

Do not reuse containers. Empty containers retain product residues can be hazardous. Follow all MSDS precautions when handling empty containers

Storage: Store in a cool, dry, well ventilated area away from incompatible materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

Potassium Hydroxide	2 mg/m3 TLV-Ceiling
Sodium Hypochlorite	None Established
Sodium Silicate	None Established
Water	None Established

Engineering Controls: Use with general or adequate local exhaust ventilation to maintain exposures below the occupational exposure limits.

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with dust/mist cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with local authority and good industrial hygiene practice.

Skin Protection: Wear impervious gloves such as butyl rubber or neoprene

Eye Protection: Chemical safety goggles and face shield should be worn where splashing is possible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: This product is a clear, colorless liquid with chlorine odor.

Physical State: Liquid	Boiling Point: 100°C
Vapor Density: Not applicable	Vapor Pressure: Not applicable
Solubility In Water: 100%	Evaporation Rate: Not applicable
Specific Gravity: 1.10-1.15	pH: 12.4 alkali
Melting Point: Not Determined	Octanol/Water Coefficient: Not Determined
VOC Content: None	Viscosity: Not Determined

10. STABILITY AND REACTIVITY

Stability: Stable under normal storage and handling conditions.

Incompatibility: Acids, most common metals and ammonia. Do not mix with other drain cleaners or ammonia as hazardous gases may be released and cause violent eruption or splashing.

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Product: Reacts with most common metals to form flammable hydrogen gas. Reacts with ammonia to form toxic gas, chloramine.

11. TOXICOLOGICAL INFORMATION

HEALTH HAZARDS:

Target Organ Effects:

Sensitization: None expected.

Chronic: Prolonged exposure to dilute solutions may cause dermatitis.

Carcinogenicity: None of the components is listed as a carcinogen or suspected carcinogen by IARC, NTP

or OSHA.

Mutagenicity: None known.

Medical Conditions aggravated by Exposure: Employees with pre-existing eye, skin and respiratory disease may be at increased risk from exposure.

Acute Toxicity Values: Potassium Hydroxide: Oral Rat LD50 - 273 mg/kg

Sodium Hypochlorite: Oral Mouse LD50 - 5800 mg/kg

Sodium Silicate: Oral Rat LD50 - 1960 mg/kg, Skin Rabbit LD50 - >4640 mg/kg

Medical Conditions aggravated by: Employees with pre-existing eye, skin and respiratory disease may be at

increased risk from exposure.

12. ECOLOGICAL INFORMATION

This material may be harmful to aquatic organisms at high concentration.

13. DISPOSAL CONSIDERATIONS

Before disposing be sure container is completely empty and rinsed with water to prevent accidental burns. Dispose in accordance with local, state and federal environmental regulations.

14. TRANSPORT INFORMATION

	DOT	TDG	MEX
Proper Shipping	Corrosive liquid,	Corrosive liquid,	Corrosive liquid,
Name:	Basic, Inorganic	Basic, Inorganic	Basic, Inorganic
	n.o.s. (Sodium	n.o.s. (Sodium	n.o.s. (Sodium
	Hypochlorite	Hypochlorite	Hypochlorite
	Potassium	Potassium	Potassium
	Hydroxide)	Hydroxide)	Hydroxide)
UN Number:	UN3266	UN3266	UN3266
Labels Required:	Corrosive	Corrosive	Corrosive
Hazard Class /	8, PG III	8, PG III	8, PG III
Packing Group:			

Note: Containers of 5 liter or less can be shipped as a Consumer Commodity ORM-D or as (Limited Quantity) in packages with a gross mass of 30 kg or less in accordance with Section 1.17 of the TDG.

15. REGULATORY INFORMATION

Inventory Status.
TSCA: Complies
DSL: Complies
NDSL: No

U.S. Federal Regulations

SARA 313.

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories Acute Health Hazard yes Chronic Health Hazard yes

Fire Hazard No Sudden Release of Pressure Hazard No Reactive Hazard No

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Sodium Hypochlorite	X	X	X
Potassium Hydroxide	Х	Х	Х

California Proposition 65

This product contains no chemicals requiring reporting under Proposition 65.

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

Canadian WHMIS: Classification: Class D-2-B (Eye and Skin Irritant)

Canadian CEPA: All the components of this product are listed on the Canadian DSL

WHMIS: Class D-2-B (Eye and Skin Irritant)

16. OTHER INFORMATION

NFPA Rating: Health = 2 Fire = 0 Reactivity = 0 **HMIS Rating:** Health = 2 Fire = 0 Reactivity = 0

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.