

# Blot-O™ Plus

## Fuel Oil Absorber



## Specifications

## Blot-O™ Plus



Shake or  
Pour Top

### DESCRIPTION

**Blot-O Plus** is a highly absorbent material utilizing a unique recycled paper material and specially selected clays to absorb more fuel oil per volume than any other absorber in its class. Sweet fragrance helps eliminate odors.

Used to clean up spills and leaks of gasoline, fuel and other oil. This product is not powder based and will not leave dusty particles in the air.

Apply **Blot-O Plus** by sprinkling on spills, leaks, tank overflows, and oil burner drips. Sweep back and forth until the spill is fully absorbed.

Dispose of used material according to local codes. **Blot-O Plus** is non-toxic.

### SIZES AND PACKING

| STOCK NO. | SIZE    | PACKING | WEIGHT/CASE |
|-----------|---------|---------|-------------|
| 35-155    | 19 oz.  | 12      | 15.6 lbs.   |
| 35-152    | 15 lbs. | 1       | 15 lbs.     |

# Blot-O™ Plus

## Fuel Oil Absorber

### APPROVALS AND LISTINGS

Not applicable.

### SPECIFIC USES

**Blot-O Plus** can be used to absorb fuel oil spills in industrial applications.

### SPECIFIC APPLICATIONS\*

Apply **Hercules Blot-O Plus** to spills and drips of fuel oil, oil and other petroleum products.

### PHYSICAL PROPERTIES

|                          |                                    |
|--------------------------|------------------------------------|
| Specific Gravity         | N/A                                |
| Solubility in water:     | Insoluble                          |
| Temperature Limitations: | 350°F                              |
| Appearance and color:    | Grey granules with perfumed scent. |

### WARNINGS OR CAUTIONS

- Read all cautions and directions carefully before using this product.
- Avoid contact with eyes and skin.
- Dispose of oil saturated materials in accordance with Federal, State and local regulations.

### DIRECTIONS FOR USE

Sprinkle **Blot-O Plus** on fuel oil spill, wait for oil to be absorbed, then sweep material back and forth over spill. Dispose of all material when all oil is absorbed.



### MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST MATERIAL SAFETY DATA SHEET (MSDS) #100

|                     |                                                                          |
|---------------------|--------------------------------------------------------------------------|
| For Delivery by Fax | Call 1-800-942-4636                                                      |
| Internet            | See MSDS section of <a href="http://www.herchem.com">www.herchem.com</a> |
| Mail                | Contact Hercules at address below or any Hercules representative         |

HMIS Hazard warning 1-0-0-E.

| INGREDIENTS            | CAS#                   |
|------------------------|------------------------|
| Cellulose/Clay Mixture | 9004-34-6 / 66402-68-4 |

\* For special applications which may not be covered on this or other Hercules literature, please contact Hercules Technical Services Department by phone at 1-800-221-9330 or send a fax to 1-800-333-3456.



**HERCULES®** <http://www.herchem.com>

### Hercules Chemical Company, Inc.

111 South Street, Passaic, NJ 07055-9100

Phone: 800-221-9330 • Fax: 800-333-3456

e-mail: [info@herchem.com](mailto:info@herchem.com)

