


Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.



MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347  
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961  
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:  
[www.zoeller.com](http://www.zoeller.com)

## DIAPHRAGM PRESSURE TANK DRAWDOWN CHARTS

### Diaphragm Air-E-Tainer® Tanks

Order No.	Model No.	Total Tank Volume Gallons	Drawdown-Gallons			Equiv. Std. Pressure Tank Gallons**	Approx. Size Inches	Ship Wt. Lbs.	NPT	Factory Precharge PSIG
			20/40	30/50	40/60					
10-2367	AT15*	4.5	1.7	1.4	1.2	12	10 x 16	10	3/4"	18
10-2368	AT44	14.0	5.2	4.3	3.8	30	16 x 22	30	1"	28
10-2369	AT66	20.0	7.4	6.2	5.4	42	16 x 29	35	1"	28
10-2370	AT122	33.4	12.3	10.3	9.0	100	16 x 43	52.5	1"	28
10-2371	AT144	44.0	16.3	13.6	11.9	120	21 x 36	66	1-1/4"	38

\* Compact in-line tank

\*\* Air-E-Tainer® tanks will deliver drawdown equivalent to conventional tanks of this size. Air-E-Tainer® tanks 100 PSI maximum working pressure.

CAUTION: Install 10-2347 pressure relief valve on any installation where pump pressure can exceed the maximum working pressure of the tank.



### Diaphragm Tank Stand

10-2372 pump stand for mounting jet pumps on top of 10-2368, 10-2369 and 10-2370 Air-E-Tainer® tanks.



10-2372

## Check and Foot Valves

**Check Valves Spring Controlled** for general service of jet, submersible or centrifugal, for horizontal or vertical application.



### Brass Check Valves

Order Number	NPT
30-0196	1"
30-0197	1-1/4"
30-0198	1-1/2"

**Foot Valves Spring Controlled** for jet or centrifugal pumps. For vertical application.



### Bronze Foot Valves

Order Number	NPT
10-2361*	1-1/4"x1"

\*Dual purpose 1" ID 1-1/4" OD threaded.

# Switches and Gauges

## Pressure Switches



**10-2376/10-2377**

Order No.	Switch Setting	Bottom Connection NPT	Maximum Electrical Rating	
			Single Phase	
			115V	230V
10-2376	20-40	1/4 M	1 HP	1-1/2 HP
10-2377	30-50	1/4 M	1-1/2 HP	2 HP
10-2378*	20-40	1/4 F	1 HP	1-1/2 HP

\* Indicates low pressure cut off for low yielding wells.

NOTE: All switches are two pole.

## Pressure Gauges

Order No.	Max. Pressure	Connection NPT
10-2379	100 PSI	1/4"
10-2380	200 PSI	1/4"



**10-2379  
10-2380**

## Submersible Well Pump Accessories



**10-2345**



**10-2344**



**10-2343 (5 per pkg.)**

Order No.	Description
10-2343	Cable guards
10-2347*	Pressure Relief Valve, 1/2" NPT, 100 PSI max.
10-2345	Submersible Torque Arrestor
10-2344	Wire Splice Kit

\*NOTE: Install a pressure relief valve with any pump capable of producing more than 75 PSI at the tank.

Some models are not for sale in states following Proposition 65 and AB1953. Alternatives are available.



**ZOELLER**  
PUMP CO.

MAIL TO: P.O. BOX 16347  
Louisville, KY 40256-0347  
SHIP TO: 3649 Cane Run Road  
Louisville, KY 40211-1961  
(502) 778-2731 • 1 (800) 928-PUMP  
FAX (502) 774-3624

Manufacturers of . .

*"QUALITY PUMPS SINCE 1939"*