



**AF1600 SYSTEM
ATHLETIC FIELD STRIPING PAINT AEROSOL**

DESCRIPTION AND USES

A fast dry, water-based inverted aerosol striping paint, designed specifically for striping athletic fields. It dries fast in 30 minutes and creates sharp, well defined lines. It is safe for use on grass, smudge resistant, durable and long-lasting.

PRODUCTS

206043	White
206045	Yellow
206044	Orange

PACKAGING

20 fl. oz. aerosol container (17 oz. weight fill)
12 aerosols/carton

PRODUCT APPLICATION

APPLICATION

Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Do not apply over dew or wet ground. Protect surrounding surfaces from overspray. Overspray can carry a significant distance.

The Athletic Field Striping sprays are designed for use with the Rust-Oleum Athletic Field Striping Machine item #206346. The Athletic Field Striping Machine has larger diameter wheels to accommodate high grass conditions. Follow machine directions for proper use.

The width of the stripe can be varied from 3 to 6 inches wide by adjusting the position of the can holder on the Striping Machine. For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping.

The athletic field striping aerosols can also be used with the #2388000 Striping Wand.

Clean valve by spraying upright for 2 to 3 seconds after each use. If valve clogs, carefully remove spray tip and clean in thinner.

Do not insert any object into can opening.

**TECHNICAL DATA****AF1600 SYSTEM ATHLETIC FIELD STRIPING PAINT AEROSOL****PHYSICAL PROPERTIES**

		ATHLETIC FIELD STRIPING PAINT
Resin Type		Modified alkyd
Pigment Type		Varies with color
Volatile Organic Compounds		<66% by weight
MIR		Maximum value of 1.2
Fill Weight		17 oz.
Practical Coverage		Approximately 100-200 linear ft. at 3" wide (30-60 m. at 7.6 cm.)
Dry Times at 70-80°F (21-27°C) and 50% Rel. Hum.	Tack-free	<5 minutes
	Full use	30 minutes
Shelf Life		5 years
Safety Information	Flash Point	Below 0°F
	Contains	Acetone, Xylene, and Toluene
	Warning!	THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. FOR INDUSTRIAL OR COMMERCIAL USE ONLY. REFER TO MATERIAL SAFETY DATA SHEET AND LITHOGRAPHED CANS FOR MORE COMPLETE SAFETY INFORMATION.

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.