

**INDUSTRIAL
— CHOICE —**BY **RUST-OLEUM®****M1900 SYSTEM
360° MARKING PAINT AEROSOL****DESCRIPTION AND USES**

A general purpose water-based marking paint that features a convenient 360° spray nozzle. Sprays in any position; inverted, horizontal or upright, making it the only can of marking paint needed for any given job or landscape. Use for marking gravel, grass, dirt, asphalt, concrete, wood, metal, rock, plastic, drywall and more. Ideal for use in a variety of industries including utility location, surveying, excavation, construction, golf courses, landscaping, mining and HVAC.

PRODUCTS**WATER-BASED**

247832	High Visibility Yellow
247833	Fluorescent Red
247834	Fluorescent Green
247835	Fluorescent Orange
247836	Fluorescent Red-Orange
247837	White

PACKAGING

20 fl. oz. aerosol container, (17 oz. weight fill),
12 aerosols/carton.

PRODUCT APPLICATION**SURFACE PREPARATION**

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating.

APPLICATION

Use when temperature is above 40°F (4°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. Hold can 4 to 10 inches from surface to be marked. Press in sideways to spray or use Rust-Oleum Marking Wand #2393000 or Marking Pistol #210188. Follow directions for proper use of this equipment. Keep can moving to prevent build-up. Wipe off spray tip when finished using. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled.

TECHNICAL DATA

M1900 SYSTEM 360° MARKING PAINT AEROSOL

PHYSICAL PROPERTIES

		360° MARKING PAINT
Resin Type		Modified Alkyd
Pigment Type		Varies with color
Volatile Organic Compounds		<66% by weight
MIR		Maximum value of 1.2
Fill Weight		17 oz.
Practical Coverage		Approximately 600-700 linear feet at 1 in. wide
Dry Times at 70°-80°F (21°-27°C) and 50% Relative Humidity		Less than 5 minutes
Shelf Life		5 years
Safety Information	Contains	Acetone, Xylene, and Toluene
	Warning!	<p>THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.</p> <p>DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. FOR INDUSTRIAL OR COMMERCIAL USE ONLY.</p> <p>REFER TO MATERIAL SAFETY DATA SHEET AND CANS FOR MORE COMPLETE SAFETY INFORMATION.</p>

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.