

**INDUSTRIAL  
— CHOICE —**BY **RUST-OLEUM®****MC1800 SYSTEM  
PRECISION LINE® INVERTED MARKING CHALK  
AEROSOL****DESCRIPTION AND USES**

An aerosol applied chalk used for temporary marking projects on concrete, pavement, gravel, grass, and more. Designed for marking where a non-permanent identification is desired. Lasts 15-30 days when undisturbed.

The MC1800 System aerosols are ideal for temporary location marking of underground utilities at construction and excavation sites, or other temporary marking applications.

**PRODUCTS**

|        |             |
|--------|-------------|
| 205233 | APWA Orange |
| 205234 | APWA Yellow |
| 205235 | APWA Red    |
| 205236 | APWA Blue   |
| 205237 | APWA White  |
| 205238 | APWA Green  |

**PACKAGING**

Inverted 20 fl. oz. aerosol container (17 oz. weight fill),  
12 aerosols/carton

**PRODUCT APPLICATION****SURFACE PREPARATION**

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating.

**APPLICATION**

Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. Shake can vigorously for one minute after mixing ball is heard. Invert can and point at ground or floor. Hold can 4 to 6 inches above surface to be marked. Press in sideways to spray or use Rust-Oleum Marking Wand item #2393000 or Rust-Oleum Marking Pistol item #210188. Follow directions for proper use of this equipment. Keep can moving to prevent build-up. Clean valve by spraying upright for 2 to 3 seconds after each use. If valve clogs, carefully remove spray tip and clean in thinner. **Do not** insert any object into can valve opening.

**REMOVAL**

Marking Chalk will normally fade through ordinary weathering in about 15 to 30 days. Earlier removal can be accomplished by washing with a stiff bristle brush and water or by pressure cleaning.

## TECHNICAL DATA

### MC1800 SYSTEM PRECISION LINE® INVERTED MARKING CHALK AEROSOL

#### PHYSICAL PROPERTIES

|                                                          |          | PRECISION-LINE INVERTED MARKING CHALK                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resin Type                                               |          | Modified alkyd                                                                                                                                                                                                                                                                                                                                                           |
| Pigment Type                                             |          | Varies with color                                                                                                                                                                                                                                                                                                                                                        |
| Volatile Organic Compounds                               |          | <66% by weight                                                                                                                                                                                                                                                                                                                                                           |
| MIR                                                      |          | Maximum value of 1.2                                                                                                                                                                                                                                                                                                                                                     |
| Fill Weight                                              |          | 17 oz.                                                                                                                                                                                                                                                                                                                                                                   |
| Practical Coverage                                       |          | Approximately 500-530 linear ft. at 1.25" wide                                                                                                                                                                                                                                                                                                                           |
| Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity |          | Scuff-resistant in approximately 10 min.                                                                                                                                                                                                                                                                                                                                 |
| Shelf Life                                               |          | 5 years                                                                                                                                                                                                                                                                                                                                                                  |
| Safety Information                                       | Contains | Acetone, Xylene, and Toluene                                                                                                                                                                                                                                                                                                                                             |
|                                                          | Warning! | <b>THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. FOR INDUSTRIAL OR COMMERCIAL USE ONLY. REFER TO MATERIAL SAFETY DATA SHEET AND LITHOGRAPHED CANS FOR MORE COMPLETE SAFETY INFORMATION.</b> |

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.