Concrete Saver®
200 ANTI-SKID ADDITIVE

DESCRIPTION A specially refined aggregate for use in floor coatings to provide an irregular surface profile, and promote skid resistance in the dry coating film.

USES Use on floors where a skid resistant finish is desired.

APPEARANCE Off-white powder or granules.

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

COMPOSITION	Silicon Oxide
SOLVENTS	None
SPECIFIC GRAVITY	2.25 g/cm^3
SHELF LIFE	Unlimited

PACKAGING One pound bags

APPLICATION The 200 Anti-Skid additive can either be mixed directly into the coating before it is applied or broadcast by hand onto coating immediately after application. Use one pound per gallon.

If the 200 Anti-Skid additive is premixed into the coating, then stir frequently during use to prevent settling. Do not premix into the coating if the coating is being applied by spray application.

The 200 Anti-Skid additive can also be broadcast by hand onto the wet coating after it has been applied. Distribute evenly, then lightly backroll with a short nap roller to anchor the additive into the coating.

**THIS PRODUCT MAY PRESENT A NUISANCE DUST HAZARD IN ITS DRY FORM.
WEAR DUST MASK AND EYE PROTECTION UNTIL POWDER IS MIXED INTO PAINT.**

KEEP OUT OF REACH OF CHILDREN.

SEE THE PRODUCT MATERIAL SAFETY DATA SHEET (MSDS) FOR ADDITIONAL SAFETY INFORMATION.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. **All technical information is subject to change without notice.**