Material Safety Data Sheet

TRADES-MARKER® WS Red

1. Product and company identification

Product name	: TRADES-MARKER [®] WS Red
Material uses	: FOR INDUSTRIAL USE ONLY Cold Surface Marking Products. Marking and Identification.
Supplier/Manufacturer	: LA-CO Industries, Inc. 1201 Pratt Boulevard Elk Grove Village, IL. 60007-5746
In case of emergency	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

This MSDS reflects the health, physical and environmental hazards of the paint released by this product. Because of the nature of the finished product i.e. the fact that the paint is in solid form, and given that the paint is released in very small amounts during normal use, the user of the product and/or the reader of this MSDS should consider the potential exposure to the paint to be minimal and controlled during the normal use of the product. Refer to relevant sections of the MSDS (7 and 13) for additional information on handling and disposal considerations.

To avoid any potential hazard and to minimize the risk of exposure, it is important that the user of the product does NOT heat, burn or expose it to a source of intense heat unless the product is specifically intended for use on hot surfaces.

Emergency overview		
Physical state	1	Solid.
Color	1	Red.
Hazard statements	:	NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.
Precautionary measures	:	No known significant effects or critical hazards. Avoid prolonged contact with eyes, skin and clothing.
OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.
Routes of entry	1	Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effects	<u>s</u>	
Inhalation	:	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	1	No known significant effects or critical hazards.
Skin	1	No known significant effects or critical hazards.
Eyes	1	No known significant effects or critical hazards.
Potential chronic health effe	cts	
Chronic effects	1	No known significant effects or critical hazards.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	1	No known significant effects or critical hazards.
Teratogenicity	1	No known significant effects or critical hazards.
Developmental effects	1	No known significant effects or critical hazards.
Fertility effects	1	No known significant effects or critical hazards.
Target organs	:	Contains material which may cause damage to the following organs: lungs, cardiovascular system, upper respiratory tract, skin, stomach.

Over-exposure signs/symptoms



2. Hazards identification

Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: No specific data.
Eyes	: No specific data.
Medical conditions aggravated by over- exposure	: None known.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
Talc	14807-96-6	10 - 30
Titanium oxide	13463-67-7	5 - 10
Kaolin	1332-58-7	1 - 5
Quartz	14808-60-7	0.1 - 1

Canada

Name	CAS number	%
Talc	14807-96-6	10 - 30
Titanium oxide	13463-67-7	5 - 10
Kaolin	1332-58-7	1 - 5
Quartz	14808-60-7	0.1 - 1

<u>Mexico</u>			
Name	CAS number	UN number	%

Name	CAS number	UN number	%	IDLH	н	F	R	Special
Talc	14807-96-6	Not regulated.	10 - 30	1000 mg/m ³	2	0	0	-
Titanium oxide	13463-67-7	Not regulated.	5 - 10	5000 mg/m ³	2	0	0	-
Kaolin	1332-58-7	Not regulated.	1 - 5	-	2	0	0	-
Silica, amorphous, fumed, crystfree	112945-52-5	Not regulated.	1 - 5	-	0	0	0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact	 Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention if symptoms occur.
Inhalation	: Move exposed person to fresh air. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.
Notes to physician	: No specific treatment. Treat symptomatically.

5. Fire-fighting measures

Flammability of the product	: No specific fire or explosion hazard.
Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.



Classification

TRADES-MARKER[®] WS Red

5. Fire-fighting measures

Hazardous decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides halogenated compounds
Special protective equipment for fire-fighters	: No special protection is required.

6. Accidental release measures

Personal precautions	: Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Small spill	: Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and Handling smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Empty containers retain product residue and can be hazardous.

Store in accordance with local regulations. Store in original container protected from Storage direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits	
Talc	NIOSH REL (United States, 6/2009). TWA: 2 mg/m ³ 10 hour(s). Form: Respirable fraction ACGIH TLV (United States, 2/2010). TWA: 0.1 f/cc 8 hour(s).	
	OSHA PEL Z3 (United States, 9/2005). STEL: 1 f/cc 30 minute(s). Form: not containing asbestos TWA: 20 mppcf 8 hour(s). Form: not containing asbestos TWA: 0.1 f/cc 8 hour(s). STEL: 1 f/cc 30 minute(s).	
Titanium oxide	OSHA PEL (United States, 6/2010). TWA: 15 mg/m ³ 8 hour(s). Form: Total dust ACGIH TLV (United States, 2/2010). TWA: 10 mg/m ³ 8 hour(s).	
Kaolin	ACGIH TLV (United States, 2/2010). TWA: 2 mg/m ³ 8 hour(s). Form: Respirable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m ³ 10 hour(s). Form: Respirable fraction	
KMK Regulatory Service	ا s Inc. Tel : +1-888-GHS-7769 (447-7769)/+1-450-GHS-7767 (447-7767); Services Réglementaires KMK Inc. www.kmkregservices.com	3/8

8. Exposure controls/personal protection

•	
	TWA: 10 mg/m ³ 10 hour(s). Form: Total
	OSHA PEL (United States, 6/2010).
	TWA: 5 mg/m ³ 8 hour(s). Form: Respirable fraction
	TWA: 15 mg/m ³ 8 hour(s). Form: Total dust
Quartz	OSHA PEL Z3 (United States, 9/2005).
	TWA: 10 mg/m ³ 8 hour(s). Form: Respirable
	TWA: 250 mppcf 8 hour(s). Form: Respirable
	TWA: 30 mg/m ³ 8 hour(s). Form: Total dust
	NIOSH REL (United States, 6/2009).
	TWA: 0.05 mg/m ³ 10 hour(s). Form: Respirable dust
	ACGIH TLV (United States, 2/2010).
	TWA: 0.025 mg/m ³ 8 hour(s). Form: Respirable fraction

Canada

Occupational expos	<u>ure limits</u>	TWA	(8 hours))	STEL	(15 mins	5)	Ceilin	g		
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Talc	US ACGIH 2/2010	-	-	0.1 f/cc	-	-	-	-	-	-	
	BC 9/2010	-	2	-	-	-	-	-	-	-	[a]
		-	-	0.1 f/cc	-	-	-	-	-	-	
	ON 7/2010	-	2	-	-	-	-	-	-	-	[b]
		-	2	2 f/cc	-	-	-	-	-	-	
	QC 6/2008	-	3	ŀ	-	-	-	-	-	ŀ	[c]
Titanium oxide	US ACGIH 2/2010	-	10	-	-	-	-	-	-	-	
	AB 4/2009	-	10	-	-	-	-	-	-	-	[3]
	BC 9/2010	-	3	-	-	-	-	-	-	-	[C]
		-	10	-	-	-	-	-	-	-	[d]
	ON 7/2010	-	10	-	-	-	-	-	-	-	[d]
	QC 6/2008	-	10	-	-	-	-	-	-	-	[d] [b]
Kaolin	US ACGIH 2/2010	-	2	-	-	-	-	-	-	-	[b]
	AB 4/2009	-	2	-	-	-	-	-	-	-	[e]
	BC 9/2010	-	2	-	-	-	-	-	-	-	[e]
	ON 7/2010	-	2	-	-	-	-	-	-	-	[e] [b]
	QC 6/2008	-	5	-	-	-	-	-	-	-	[C]
Quartz	US ACGIH 2/2010	-	0.025	-	-	-	-	-	-	-	[b]
	AB 4/2009	-	0.025	-	-	-	-	-	-	ŀ	[b] [f]
	BC 9/2010	-	0.025	-	-	-	-	-	-	ŀ	[a] [b] [c]
	ON 7/2010	-	0.1	-	-	-	-	-	-	\mathbf{F}	[b]
	QC 6/2008	-	0.1	ŀ	-	-	-	-	-	ŀ	[c]
						1					

[3]Skin sensitization Form: [a]Respirable. [b]Respirable fraction [c]Respirable dust [d]Total dust [e]Respirable [f]Respirable particulate.

Mexico

Occupational exposure limits

Ingredient	Exposure limits
Talc	NOM-010-STPS (Mexico, 9/2000).
	LMPE-PPT: 2 mg/m ³ 8 hour(s).
Titanium oxide	NOM-010-STPS (Mexico, 9/2000).
	LMPE-CT: 20 mg/m ³ , (as Ti) 15 minute(s).
	LMPE-PPT: 10 mg/m ³ , (as Ti) 8 hour(s).
Silica, amorphous, fumed, crystfree	NOM-010-STPS (Mexico, 9/2000).
	LMPE-PPT: 3 mg/m ³ 8 hour(s). Form: breathable particulates
	LMPE-PPT: 10 mg/m ³ 8 hour(s). Form: inhalable particulates
Kaolin	NOM-010-STPS (Mexico, 9/2000).
	LMPE-CT: 20 mg/m ³ 15 minute(s).
	LMPE-PPT: 10 mg/m ³ 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	: Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Engineering measures	: Use only with adequate ventilation.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.
Bana and an effect of the second	

Personal protection



8. Exposure controls/personal protection

•	• •
Respiratory	 Not required for normal use of the pen/marker. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	 Not required for normal use of the pen/marker. Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).
Eyes	: Not required for normal use of the pen/marker. Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses with side shields.
Skin	: Not required for normal use of the pen/marker. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Lab coat.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

Physical state	:	Solid.
Color	:	Red.

10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: No specific data.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials and acids.
Hazardous decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides halogenated compounds
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

: No specific data.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Talc Titanium oxide	Skin - Mild irritant Skin - Mild irritant	Human Human	-	72 hours 300 Micrograms Intermittent 72 hours 300 Micrograms Intermittent	-

Carcinogenicity

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Talc	A4	1	-	None.	-	-
Titanium oxide	A4	2B	-	None.	-	-
Kaolin	A4	-	-	-	-	-
Quartz	A2	2A	-	+	Proven.	-
IDLH	: Not availab	ole.	•		•	

Synergistic products

: Not available.



12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Product/ingredient name	Result	Species	Exposure
Titanium oxide	Acute EC50 5.83 mg/L Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute LC50 5.5 ppm Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
	Acute LC50 >1000000 ug/L Marine water	Fish - Fundulus heteroclitus	96 hours
	Chronic NOEC 1 ppm Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

International transport regulations DOT/TDG/MXT/IMDG/IATA : Not regulated.

T/TDG/MAT/IMDG/IATA : Not regulate

15. Regulatory information

United States	
HCS Classification	: Not regulated.
U.S. Federal regulations	 TSCA 8(a) IUR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): Not determined.
	SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Talc; Kaolin; Titanium oxide SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Talc: Immediate (acute) health hazard; Kaolin: Delayed (chronic) health hazard; Titanium oxide: Delayed (chronic) health hazard
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed



TRADES-MARKER[®] WS Red

15. Regulatory information

: Not listed

DEA List II Chemicals (Essential Chemicals)

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Barium 4-[(5-chloro-4-methyl-2-sulphonatophenyl)azo]-3- hydroxy-2-naphthoate	7585-41-3	5 - 10
Supplier notification	Barium 4-[(5-chloro-4-methyl-2-sulphonatophenyl)azo]-3- hydroxy-2-naphthoate	7585-41-3	5 - 10

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulationsMassachusetts: The following components are listed: Talc; Titanium oxideNew York: None of the components are listed.New Jersey: The following components are listed: Talc; Quartz; Titanium oxide; Barium 4-[(5-chloro-
4-methyl-2-sulphonatophenyl)azo]-3-hydroxy-2-naphthoate; KaolinPennsylvania: The following components are listed: Talc; Quartz; Titanium oxide; Barium 4-[(5-chloro-
4-methyl-2-sulphonatophenyl)azo]-3-hydroxy-2-naphthoate; Kaolin

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	• •	Maximum acceptable dosage level
Quartz (*)	Yes.	No.	No.	No.

(*) These ingredients are not expected to be present as unbound, respirable particles during normal use of this product.

<u>Canada</u>							
WHMIS (Canada)	1	Not controlled under WHMIS (Canada).					
Canadian lists							
Canadian NPRI	1	None of the components are listed.					
CEPA Toxic substances	1	None of the components are listed.					
Canada inventory	1	Not determined.					
This product has been classified in accordance with the hazard criteria of the Controlled F							

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico
Classification : Health Image: Classification International regulations
International lists : International regulations
International lists : Australia inventory (AICS): Not determined.
China inventory (IECSC): All components are listed or exempted.
Japan inventory: Not determined.
Korea inventory: All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.



TRADES-MARKER[®] WS Red

16. Other information

Label requirements : NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.										
Hazardous Material Information System (U.S.A.)		Health :	1	Flammability :	0	Physical hazards :	0			
Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or										

risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection : Health : 1 Flammability : 0 Instability : 0 Association (U.S.A.)

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History Date of issue mm/dd/yyy : 15/08/2011 Version : 1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

