

Patent pending

New & Improved! RINGCRUSHER™ Decrimping Tool



- Removes crimp ring and PEX tubing from fittings in seconds!
- New cushion-grip handle.
- New heavy-duty tool head with rounded anvil cuts fast. Prevents damage to inside fittings.
- No more hacksaw, torch or frustration.
- Will not damage PEX fittings when used properly.
- Lets you recycle brass & poly alloy/plastic fittings.



RINGCRUSHER cuts crimp rings off fittings and expands crimped tubing for easy removal. It only takes a few seconds. New heavy-duty design cuts crimp rings on 1/2", 3/4" and 1" copper, brass and poly alloy/plastic fittings and tube without damage to inside fittings. Stop wasting time using a hack-saw or torch, and stop throwing away expensive PEX fittings.



- 1. Cut off PEX tube close to the fitting. Insert small jaw inside fitting and fully close handles, forcing cutter through crimp ring.
- 2. Reposition cutter to uncut side of ring and partially close handles, forcing crimp ring open. Repeat in another position to free ring for removal.
- 3. Reinsert Ringcrusher into fitting; fully close the handles, forcing the cutting jaw into PEX pipe. Repeat in several positions to free PEX pipe for removal.



Periodically adjust RINGCRUSHER

A properly adjusted tool will allow the edge of a 3/4" fitting to closely pass between the jaws of the tool when handles are fully closed. To adjust, loosen lock nut, turn stop screw and retighten lock nut.



Mill-Rose is not responsible for misuse of the tool, the RINGCRUSHER, or use of damaged fittings in work. Avoid using damaged fittings. Follow instructions when using this tool; periodically check and adjust the stop.

Cat.	Description	Std. Pk.	Weight
73015	POP display packaged	5	3.79 lbs.
73020	POP Display (10)	1	6.75 lbs.



point-of-purchase display

7310 Corporate Blvd., Mentor, OH 44060