

MATERIAL SAFETY DATA SHEET

SECTION 1 – PRODUCT INFORMATION

Supplier Name

The Mill-Rose Company
7310 Corporate Blvd.
Mentor, OH 44060

Emergency Telephone No.

(800) 321-3598

Date Prepared: April 1, 2012

Replaces: June, 2007

Product

Industrial Oil, petroleum hydrocarbon

Trade Names and Synonyms

Turbine Oiler With Zoom Spout™

SECTION 2 – EMERGENCY OVERVIEW

For Chemical Emergencies:

Spill, leak, fire or accident call CHEMTREC
North America (800) 424-9300
Others: (703) 527-3887 (collect)

For Health Emergencies:

California Poison Control System
Continental US: (800) 356-3129
Outside US: (415) 821-5338

Health Hazards: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Physical Hazards: Keep away from all sources of ignition

Physical Form: Liquid

Appearance: Clear yellow

Odor: Characteristic petroleum

NFPA Hazard Class: Health: 1 (Slight)

Flammability: 1 (Slight)

Reactivity: 0 (Least)

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	% Volume	Exposure Guideline		
		Limits	Agency	Type
Oil Mist, If Generated CAS #: None		5 mg/m3	ACGIH	TWA
		10 ppm	ACGIH	STEL
		5 mg/m3	OSHA	TWA
Other Components	% Volume	Exposure Guideline		
		Limits	Agency	Type
Lubricant base oil (Petroleum) CAS #: Various	99-100	See: Oil mist, if generated		
Additives CAS#: Proprietary	0-1	Not established		

The base oil for this product can be a mixture of any of the following highly refined petroleum streams:
CAS 64741-88-4; CAS 64741-89-5; CAS 64741-96-4; CAS 64741-97-5; CAS 64742-01-4; CAS 64742-52-5; CAS 64742-53-6; CAS 64742-54-7; CAS 64742-55-8; CAS 64742-56-9; CAS 64742-57-0; CAS 64742-58-1; CAS 64742-62-7; CAS 64742-63-8; CAS 64742-65-0; CAS 72623-85-9; CAS 72623-86-0; CAS 72623-87-1

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies for further information.

SECTION 4 – HAZARDS IDENTIFICATION

Potential Health Effects:

Eye: Contact may cause mild eye irritation including stinging, watering and redness.

Skin: Contact may cause mild skin irritation including redness, burning sensation, and drying and cracking of skin. No harmful effects from skin absorption are expected.

Inhalation (Breathing): No information available. Studies by other exposure routes suggest a low degree of toxicity by inhalation.

Ingestion (Swallowing): No harmful effects expected from ingestion

Signs and Symptoms: Effects of overexposure may include irritation of the nose and throat, irritation of the digestive tract, nausea and diarrhea.

Cancer: Inadequate evidence available to evaluate the cancer hazard of this material. See Section 12 for carcinogenicity information of individual components, if any.

Target Organs: None

Developmental: No data available for this material. See Section 12 for developmental toxicity information of individual components, if any.

Pre-Existing Medial Conditions: Conditions aggravated by exposure may include skin disorders.

SECTION 5 – FIRST AID MEASURES

Eye: If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.

Skin: Wipe material from skin and remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water and, if necessary, a waterless skin cleanser. If irritation or redness develops and persists, seek medical attention.

Inhalation (Breathing): If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion (Swallowing): First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

Notes to Physicians: High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. Often these injuries require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury.

SECTION 6 – FIRE FIGHTING MEASURES

Flammable Properties:

Flash Point: >365°F/>185°C (COC)

OSHA Flammability Class: Not applicable

LEL/UEL%: No data

Autoignition Temperature: No data

Unusual Fire & Explosion Hazards: This material may burn, but will not ignite readily. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

Extinguishing Media: Dry chemical, carbon dioxide, foam or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Fire Fighting Instructions: For fires beyond the incipient stage, emergency responders in the immediate

hazard area should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces or when explicitly required by DOT, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (See Section 9).

SECTION 7 – ACCIDENTAL RELEASE MEASURES

This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (See Section 9).

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Dike far ahead of spill for later recovery or disposal. Spilled material may be absorbed into an appropriate absorbent material.

Notify fire authorities and appropriate federal, state and local agencies. Immediate cleanup of any spill is recommended. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center at (800) 424-8802.

SECTION 8 – HANDLING AND STORAGE

Handling: Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. The use of appropriate respiratory protection is advised when concentrations exceed any established exposure limits (see sections 3 & 9)

Do not wear contaminated clothing or shoes. Use good personal hygiene practice. High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing of high pressure hydraulic oil equipment.

“Empty” containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. “Empty” drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1 and other references pertaining to cleaning, repairing, welding or other contemplated operations.

Storage: Keep container(s) tightly closed. Use and store this material in cool, dry, well-ventilated areas away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (see Section 11). Protect container(s) against physical damage.

SECTION 9 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: If current ventilation practices are not adequate to minimize exposure, additional ventilation or exhaust systems may be required.

Personal Protection Equipment (PPE):

Respiratory: A NIOSH certified air purifying respirator with a dust/mist filter may be used under conditions where airborne concentrations are expected to exceed exposure limits (see Section 3) Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release,

exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirators use.

Permissible Exposure Levels: Refer to Section 2 for information about the PEL for ingredients

Skin: The use of gloves impervious to the specific material handled is advised to prevent skin contact and possible irritation (see manufacturers literature for information on permeability)

Eye/Face: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended. Depending on conditions of use, a face shield may be necessary.

Other Protective Equipment: A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

SECTION 10 – PHYSICAL AND CHEMICAL PROPERTIES

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm HG (1atm)

Flash Point: >365°F / >185°C (COC)

Flammable/Explosive Limits (%): No data

Autoignition Temperature: No data

Appearance: Clear yellow

Physical State: Liquid

Odor: Characteristic petroleum

pH: Not applicable

Vapor Pressure (mm Hg): No data

Vapor Density (air=1): >1

Boiling Point/Range: >555°F / >291°C

Freezing/Melting Point: No data

Solubility in Water: Negligible

Specific Gravity: 0.86 - 0.88

Percent Volatile: Negligible

Evaporation Rate (nBuAc=1): <1

Viscosity: 5.47 cSt @ 100°C / 32.2 cSt @ 40°C

Bulk Density: 7.33 lbs/gal

SECTION 11 – STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of storage and handling

Conditions to Avoid: Extended exposure to high temperatures can cause decomposition

Incompatible Materials: Avoid contact with strong oxidizing agents

Hazardous Decomposition Products: Combustion can yield aldehydes and carbon, nitrogen and sulfur oxides. Thermal decomposition may produce hydrogen sulfide and other sulfur-containing gases at temperatures greater than 150°F

Hazardous Polymerization: Will not occur.

SECTION 12 – TOXICOLOGICAL INFORMATION

Lubricant Base Oil (Petroleum) (CAS# Various)

Carcinogenicity: The petroleum base oils contained in this product have been highly refined by a variety of processes including solvent extraction, hydrotreating, and de-waxing to remove aromatics and improve performance characteristics. None of the oils used are listed as a carcinogen by NTP, IARC or OSHA.

SECTION 13 – DISPOSABLE CONSIDERATIONS

This material under most intended uses would become used oil due to contamination by physical or chemical impurities. Recycle all used oil. While being recycled, used oil is regulated by 40CFR 279. Use resulting in chemical or physical change or contamination may also subject it to regulation as hazardous waste. Under federal regulations, used oil is a solid waste managed under 40CFR 279. However, in California, used oil is managed as hazardous waste until tested to show it is not hazardous. Consult state and local regulations regarding the proper handling of used oil. In the case of used oil, the intent to discard it may cause the used oil to be regulated as hazardous waste.

Contents should be completely used and containers emptied prior to discard. Rinsate may be considered a RCRA hazardous waste and must be disposed of with care and in compliance with federal, state and local regulations. Large empty containers, such as drums, should be returned to the distributor or a drum reconditioner. To assure proper disposal of small empty containers, consult with state and local regulations and disposal authorities.

SECTION 14 – TRANSPORT INFORMATION

Hazard Class or Division: Not classified as hazardous.

SECTION 15 – REGULATORY INFORMATION

This material contains the following chemicals subject to the reporting requirements of SARA 313 and 40CFR 372: None

Warning: This material contains the following chemicals which are known to the state of California to cause cancer, birth defects or other reproductive harm and are subject to the requirements of California Proposition 65 (CA Health and Safety Code Section 25249.5): None known

This material has not been identified as a carcinogen by NTP, IARC, or OSHA. See Section 12 for carcinogenicity information of individual components, if any.

EPA (CERCLA) Reportable Quantity: None

NOTICE FROM THE MILL-ROSE COMPANY

The information in this Material Safety Data Sheet (MSDS) relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. We believe that the information contained herein is current as of the date of the MSDS. Since use of this information and these opinions and the conditions of use of the product are not within the control of The Mill-Rose Company, it is the user's obligation to determine the conditions of safe use of the product.