

200 PSI CWP Bronze Gate Valves


Bronze Body • Screw-in Bonnet • Non-Rising Stem • Solid Wedge • Compact Design • Full Port

200 PSI/14 Bar Non-Shock Cold Working Pressure

MATERIAL LIST

PART	SPECIFICATION
1. Handwheel Screw	Stainless Steel, Type 430
2. Handwheel	Aluminum
3. Stem	Bronze ASTM B 99 Alloy C65100 H04
4. Stem O-Ring	EPDM
5. Bonnet	Cast Brass ASTM B 584 Alloy C84400
6. Wedge	Cast Brass ASTM B 584 Alloy C84400
7. Body	Cast Brass ASTM B 584 Alloy C84400


Size	Dimensions						Weight			
	A		B		C		T-29		S-29	
In. mm.	In.	mm.	In.	mm.	In.	mm.	Lbs.	Kg.	Lbs.	Kg.
1/2	15	1.81	46	2.52	64	0.81	.21	.48	.42	.19
3/4	20	2.00	51	2.83	72	0.88	.22	.75	.65	.30
1	25	2.31	59	3.27	83	1.06	.25	1.22	.55	.50
1 1/4	32	2.63	69	3.64	92	1.13	.29	1.62	.74	.63
1 1/2	40	2.75	70	4.16	106	1.19	.29	2.12	.96	.90
2	50	2.88	73	4.88	124	1.31	.33	3.29	1.49	1.47




T-29
Threaded



S-29
Solder



T-29
NPT x NPT



S-29
Cup x Cup