Carbon Chain Heavy Duty Tiedowns

G80 & G100 Heavy Duty Tiedowns



| Chain Size | Chain Grade | Working Load Limit | Product Code | L | Finish | App. Weight |
|------------|----------------|-----------------------|--------------|-----|--------|-------------|
| Imperial | | | | | | |
| in. | | lb. | | ft. | | lb. |
| 3/8 | 80 | 7,100 | 607037CL20 | 20 | Black | 31 |
| 3/8 | 80 | 7,100 | 607037CL25 | 25 | Black | 38 |
| 1/2 | 80 | 12,000 | 607050CL15 | 15 | Black | 42 |
| 1/2 | 80 | 12,000 | 607050CL20 | 20 | Black | 55 |
| 3/8 | 100 | 8,800 | 607337CL20 | 20 | Gray | 31 |
| 3/8 | 100 | 8,800 | 607337CL25 | 25 | Gray | 38 |



- Meets FMCSA, CVSA tiedown requirements
- Made from high quality alloy steel
- Permanent identification on chain and attachments
- · Recommended chain for heavy equipment
- Made to order assemblies available in 3 days or less

AWARNING A

Death/injury can occur from improper use or maintenance of tie-down equipment.

To avoid injury:

- Inspect before use. Remove from service if cracked, worn, or deformed.
- Do not overload. Load binders develop approximate working load with hand effort.
- Do not use handle extender on load binder(s).
- Do not use binder components for overhead lifting.