

For Residential and Commercial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

Series LF3006 Dielectric Unions

Sizes: ½" – 2" (15 – 50mm)

Series LF3006 Dielectric Unions feature a female iron pipe thread to female iron pipe thread (black). These unions are designed to be installed between pipe made from dissimilar metals to prevent accelerated corrosion and deterioration in the piping system due to galvanic and stray current. The LF3006 features Lead Free* construction to comply with Lead Free* installation requirements.

Features

- Female iron pipe thread to female iron pipe thread (black)
- Designed and manufactured to the highest quality standards
- Individually factory certified to withstand a minimum of 600 volts on a dry line with no flashover
- Rated to 180°F (82°C) at 250psi (17.2 bar)

Specifications

A dielectric union shall be installed where indicated on the plans. The union shall feature a female iron pipe thread to female iron pipe thread (black). The union shall be a Watts Series LF3006.


LF3006

Standards

Meets federal specifications for tensile strength and thread end connections


Pressure — Temperature

Maximum Pressure: 250psi (17.2 bar)

Maximum Temperature: 180°F (82°C)

Options

GB - Optional EPDM gasket for use in steam or hot water applications up to 300F.



Materials — Dimensions — Weights

SIZE		MATERIALS					DIMENSIONS				WEIGHT	
in.	mm	TAIL PIECE	ADAPTER †	NUT †	INSULATOR	GASKET **	A		B		oz.	gm.
½	15	Steel	Steel	Steel	Polysulfone	Buna-N	1⅝	41	2¼	57	7.7	218
¾	20	Steel	Steel	Steel	Polysulfone	Buna-N	1⅞	48	2¼	57	11	312
1	25	Steel	Steel	Steel	Polysulfone	Buna-N	2¼	58	2½	64	11	312
1¼	32	Steel	Steel	Steel	Polysulfone	Buna-N	2¾	70	2¾	70	23.4	663
1½	40	Malleable Iron	Malleable Iron	Malleable Iron	Polysulfone	Buna-N	3½	89	2¾	70	43.4	1230
2	50	Malleable Iron	Malleable Iron	Malleable Iron	Polysulfone	Buna-N	4⅞	105	3⅞	79	43.4	1230

† Steel and malleable iron components are zinc plated

** Optional Gasket B (GB)- EPDM Gasket for use in steam or hot water applications up to 300 F (149 C) at 50 psi (3.4 bar).

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: Tel: (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca

A Watts Water Technologies Company