For Residential and Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative
.pp. 313.	

Series FH

Frost-proof Automatic Draining Wall Hydrants

Sizes: ½" x ½", ¾" x ½", ¾" x ¾" (15 x 15, 20 x 15, 20 x 20mm)

Series FH Frost-proof Automatic Draining Wall Hydrants are designed to provide freeze protection for external water supply.

Features

- Self drains automatically
- · Positive seat water shut-off
- 3/4" hose outlet

Models

FH-1-M1


For wall sizes: 4" - 14" (100 - 350mm), ½" (15mm) solder or ½" (15mm) male IPS inlet.


FH-1-M1-PEX

For wall sizes: 4" - 14" (100 - 350mm), $\frac{1}{2}" (15mm)$ PEX inlet.

Specifications

A frost-proof automatic draining wall hydrant to be installed where indicated in the plans. Hydrant to be manufactured of a nickel-plated brass body with a metal handle. Plastic handles are not acceptable. Hydrant to be either solder, IPS, or PEX inlet by $^3\!\!/^{\!\!\!4}$ " (20mm) hose outlet. Hydrant to be a Watts Series FH.





Dimensions - Weights

MODEL	SI	ZE	DIMENSIONS				WEIGHT		
			A		В				
	in.	mm	in.	mm	in.	mm	lbs.	kgs.	
Inlet ½" (15mm) solder or ½" (15mm) male IPS									
FH-1-M1	4	100	4 ¹⁵ / ₁₆	125	315/32	88	0.93	0.42	
FH-1-M1	6	150	7	178	315/32	88	1.00	0.45	
FH-1-M1	8	200	8	203	315/32	88	1.05	0.48	
FH-1-M1	10	250	11	279	315/32	88	1.08	0.49	
FH-1-M1	12	300	13	330	315/32	88	1.13	0.51	
FH-1-M1	14	350	15	381	315/32	88	1.20	0.54	
Inlet ½" (15mm) PEX									
FH-1-M1-PEX	4	100	5½	140	315/32	88	0.93	0.42	
FH-1-M1-PEX	6	150	71/2	191	315/32	88	1.00	0.45	
FH-1-M1-PEX	8	200	81/2	216	315/32	88	1.05	0.48	
FH-1-M1-PEX	10	250	11½	293	315/32	88	1.08	0.49	
FH-1-M1-PEX	12	300	13½	344	315/32	88	1.13	0.51	
FH-1-M1-PEX	14	350	15½	395	315/32	88	1.20	0.54	

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.





USA: No. Andover, MA • Tel: (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com Canada: Burlington, ON • Tel: (905) 332-4090 • Fax: (905) 332-7068 • www.wattscanada.ca A Watts Water Technologies Company