

For Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

PURE WATER

Model PWRO4ZRO

Zero Waste Reverse Osmosis System

ZRO-4 Zero Waste RO System

The all new patented Zero Waste Point-of-Use Reverse Osmosis System is the first ever that wastes no water. Comparable systems typically waste up to 4-12 gallons for every gallon of RO water produced. This Watts highly efficient RO system provides better-than-bottled water quality for residential applications.

Features

- 4-Stage Filtration System
 - Stage 1: Sediment Filter removes particulates down to 1 micron
 - Stage 2: Carbon Block Filter removes chlorine taste and odors
 - Stage 3: Advanced TFC Membrane rejects impurities down to 1/10,000th of a micron
 - Stage 4: Activated Carbon Final Filter serves as a final polish to remove any trace residuals.
- Re-use of rinsewater (no waste)
- 50 gallons per day TFC membrane
- Upgraded Watts top mount faucet
- 3-Gallon Storage Tank

Versatility

- No faucet air gap or drain connection required.
- Space saving design, installs under sink or in limited space.
- Adapt-A-Valve™ easily connects to water source.
- Ideal for low pressure or well applications.

Reliability

- Advanced design uses patented technology and high-quality components to ensure years of continuous operations with trouble-free performance.
- As with all of the products in the Watts family, the Zero Waste RO is backed by Watts reputation of excellence
- Economical and environmentally friendly
- 100% Efficient - No wasted water
- Saves as much as 7,000 gallons per year in a typical residential application.
- Delivers high-quality drinking water for pennies a day.



PWRO4ZRO



System tested and certified by NSF International against NSF/ANSI Standard 58 for the reduction of the claims specified on the performance data sheet.

Note: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



System tested and certified by WQA against NSF/ANSI Standard 372 for "lead free" compliance

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

WATTS®

System Specifications

Temperature: Minimum 40°F (4.4C),
Maximum 100°F (37.8C)

Pressure: Minimum 40psi (2.8kg/cm2),
Maximum 85psi (6.0 kkg/cm2)

pH: Minimum 2, Maximum 11

Iron (Fe): Max 1.0 ppm

TDS (Total Dissolved Solids): <1800ppm

Turbidity: <5 NTU

Unit Dimensions: Approx. 20" W x 18" H x 6" D

Replacement Filter Packs

MODEL	FREQUENCY	DESCRIPTION
PWFPKSEDCB	6 Months	Includes sediment and carbon filter only
PWFPK4R04		Includes all filters and membrane
PWMEM50	2 - 5 years	50 gallon per day membrane
PWILGAC10	Annually	10" final in-line filter

Note: Water conditions may require more frequent cartridge replacement



A Watts Water Technologies Company



USA: Tel. (800) 224-1299 • www.watts.com
Canada: Tel. (888) 208-8927 • www.watts.ca