

FIG. 7053

11 1/4° Elbow




FIGURE 7053 11 1/4° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	1 3/8	0.3
25	33.4	35	0.1
1 1/4	1.660	1 3/8	0.5
32	42.2	35	0.2
1 1/2	1.900	1 3/8	0.7
40	48.3	35	0.3
2	2.375	1 3/8	0.9
50	60.3	35	0.4
2 1/2	2.875	1 1/2	1.5
65	73.0	38	0.7
3	3.500	1 1/2	2.0
80	88.9	38	0.9
3 1/2	4.000	1 3/4	2.8
90	101.6	44	1.3
4	4.500	1 3/4	3.3
100	114.3	44	1.5
5	5.563	2	5.0
125	141.3	51	2.3
6	6.625	2	6.5
150	168.3	51	2.9
8	8.625	2	10.0
200	219.1	51	4.5
10	10.750	2 1/8	14.5
250	273.1	54	6.6
12	12.750	2 1/4	18.7
300	323.9	57	8.5
14	14.000	3 1/2	32.1
350	355.6	89	14.6
16	16.000	4	42.0
400	406.4	102	19.1
18	18.000	4 1/2	53.2
450	457.2	114	24.1
20	20.000	5	65.7
500	508.0	127	29.8
24	24.000	6	96.0
600	609.6	152	43.5

FIG. 7050LR

90° Long Radius Elbow*




FIGURE 7050 LR LONG RADIUS 90° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	3 1/2	0.9
25	33.4	89	0.4
1 1/4	1.660	3 7/8	1.3
32	42.2	98	0.6
1 1/2	1.900	4 1/4	1.7
40	48.3	108	0.8
2	2.375	4 3/8	2.5
50	60.3	136	1.1
2 1/2	2.875	5 3/4	4.9
65	73.0	146	2.2
3	3.500	5 7/8	6.5
80	88.9	181	2.9
3 1/2	4.000	7 1/4	9.7
90	101.6	184	4.4
4	4.500	7 1/2	11.5
100	114.3	191	5.2
5	5.563	9 1/2	20.9
125	141.3	241	9.5
6	6.625	10 3/4	29.1
150	168.3	273	13.2
8	8.625	15	59.2
200	219.1	381	26.9
10	10.750	18	104.0
250	273.1	457	47.2
12	12.750	21	147.0
300	323.9	533	66.7
14	14.000	21	169.0
350	355.6	533	76.7
16	16.000	24	222.0
400	406.4	610	100.7
18	18.000	27	280.0
450	457.2	686	127.0
20	20.000	30	344.0
500	508.0	762	156.0
24	24.000	36	490.0
600	609.6	914	222.3

FIG. 7051LR

45° Long Radius Elbow*




FIGURE 7051 LR LONG RADIUS 45° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	2 1/2	0.7
25	33.4	64	0.3
1 1/4	1.660	2 1/2	1.0
32	42.2	64	0.5
1 1/2	1.900	2 1/2	1.2
40	48.3	64	0.5
2	2.375	2 3/4	1.7
50	60.3	70	0.8
2 1/2	2.875	3	2.9
65	73.0	76	1.3
3	3.500	3 3/8	4.3
80	88.9	86	2.0
3 1/2	4.000	3 1/2	5.3
90	101.6	89	2.4
4	4.500	4	7.2
100	114.3	102	3.3
5	5.563	5	12.2
125	141.3	127	5.5
6	6.625	5 1/2	17.4
150	168.3	140	7.9
8	8.625	7 1/4	34.0
200	219.1	184	15.4
10	10.750	8 1/2	57.4
250	273.1	216	26.0
12	12.750	10	82.6
300	323.9	254	37.5
14	14.000	8 3/4	92.0
350	355.6	222	41.7
16	16.000	10	117.0
400	406.4	254	53.1
18	18.000	11 1/4	146.0
450	457.2	286	66.2
20	20.000	12 1/2	179.0
500	508.0	317	81.2
24	24.000	15	255.0
600	609.6	381	115.7

C - Cast malleable or ductile iron, all others are fabricated steel.

* 14"-24" Standard Radius 90° & 45° Elbows are 1 1/2.

Center to end dimensions and weights may differ from those shown in chart, Contact an Anvil Representative for more information.



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

PROJECT INFORMATION

APPROVAL STAMP

Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	