

FIG. 7050

90° Elbow*




FIGURE 7050 90° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	2 1/4 C	0.6
25	33.4	57	0.3
1 1/4	1.660	2 3/4 C	1.0
32	42.2	70	0.5
1 1/2	1.900	2 3/4 C	1.2
40	48.3	70	0.5
2	2.375	3 1/4 C	1.7
50	60.3	83	0.8
2 1/2	2.875	3 3/4 C	2.6
65	73.0	95	1.2
3 O.D.	2.996	4 C	3.6
76.1	76.1	102	1.6
3	3.500	4 1/4 C	4.0
80	88.9	108	1.8
3 1/2	4.000	4 1/2 C	5.5
90	101.6	114	2.5
4 1/4 O.D.	4.250	4 3/4 C	7.7
108.0	108.0	121	3.5
4	4.500	5 C	7.7
100	114.3	127	3.5
5 1/4 O.D.	5.236	5 1/4 C	10.4
133.0	133.0	133	4.7
5 1/2 O.D.	5.500	5 1/4 C	10.9
139.7	139.7	133	4.9
5	5.563	5 1/2 C	11.1
125	141.3	140	5.0
6 1/4 O.D.	6.259	6 C	15.2
159.0	159.0	152	6.9
6 1/2 O.D.	6.500	6 1/2 C	17.4
165.1	165.1	165	7.9
6	6.625	6 1/2 C	16.5
150	168.3	165	7.5
8	8.625	7 3/4 C	30.6
200	219.1	197	13.9
10	10.750	9 C	53.5
250	273.1	229	24.3
12	12.750	10 C	82
300	323.9	254	37.2
14	14.000	21	169.0
350	355.6	533	76.7
16	16.000	24	222.0
400	406.4	610	100.7
18	18.000	27	280.0
450	457.2	686	127.0
20	20.000	30	344.0
500	508.0	762	156.0
24	24.000	36	490.0
600	609.6	914	222.3

FIG. 7051

45° Elbow*




FIGURE 7051 45° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	1 3/4 C	0.5
25	33.4	44	0.2
1 1/4	1.660	1 3/4 C	0.7
32	42.2	44	0.3
1 1/2	1.900	1 3/4 C	0.9
40	48.3	44	0.4
2	2.375	2 C	1.5
50	60.3	51	0.7
2 1/2	2.875	2 1/4 C	1.9
65	73.0	57	0.9
3 O.D.	2.996	2 1/2 C	2.2
76.1	76.1	64	1.0
3	3.500	2 1/2 C	3.3
80	88.9	64	1.5
3 1/2	4.000	2 3/4 C	4.3
90	101.6	70	2.0
4 1/4 O.D.	4.250	2 3/4 C	4.4
108.0	108.0	83	2.0
4	4.500	3 C	5.4
100	114.3	76	2.4
5 1/4 O.D.	5.236	3 1/4 C	7.3
133.0	133.0	83	3.3
5 1/2 O.D.	5.500	3 1/4 C	7.8
139.7	139.7	83	3.5
5	5.563	3 1/4 C	9.0
125	141.3	83	4.1
6 1/4 O.D.	6.259	3 1/2 C	10.1
159.0	159.0	89	4.6
6 1/2 O.D.	6.500	3 1/2 C	11.1
165.1	165.1	89	5.0
6	6.625	3 1/2 C	11.2
150	168.3	89	5.1
8	8.625	4 1/4 C	19.8
200	219.1	108	9.0
10	10.750	4 3/4 C	34.3
250	273.1	121	15.6
12	12.750	5 1/4 C	50.0
300	323.9	133	22.7
14	14.000	8 3/4	92.0
350	355.6	222	41.7
16	16.000	10	117.0
400	406.4	254	53.1
18	18.000	11 1/4	146.0
450	457.2	286	66.2
20	20.000	12 1/2	179.0
500	508.0	317	81.2
24	24.000	15	255.0
600	609.6	381	115.7

FIG. 7052

22 1/2° Elbow




FIGURE 7052 22 1/2° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	3 1/4	0.5
25	33.4	83	0.2
1 1/4	1.660	1 3/4	0.7
32	42.2	44	0.3
1 1/2	1.900	1 3/4	0.8
40	48.3	44	0.4
2	2.375	1 7/8 C	1.5
50	60.3	48	0.7
2 1/2	2.875	2	1.9
65	73.0	51	0.9
3	3.500	2 1/4 C	3.2
80	88.9	57	1.5
3 1/2	4.000	2 1/2	4.0
90	101.6	64	1.8
4	4.500	2 5/8 C	5.3
100	114.3	67	2.4
5	5.563	2 7/8	7.2
125	141.3	73	3.3
6	6.625	3 1/8 C	8.2
150	168.3	79	3.7
8	8.625	3 3/8 C	17.8
200	219.1	98	8.1
10	10.750	4 1/8	30.0
250	273.1	111	13.6
12	12.750	4 7/8	40.4
300	323.9	124	18.3
14	14.000	5	46.0
350	355.6	127	20.9
16	16.000	5	52.2
400	406.4	127	23.7
18	18.000	5 1/2	65.0
450	457.2	140	29.5
20	20.000	6	80.0
500	508.0	152	36.3
24	24.000	7	112.0
600	609.6	178	50.8

7052i

22 1/2° Elbow




FIGURE 7052i 22 1/2° ELBOW*			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	1 5/8	0.5
25	33.4	41.28	0.227
1 1/4	1.675	1 3/4	1.0
32	42.2	44.45	0.454
1 1/2	1.900	1 3/4	1.0
40	48.3	44.45	0.454
2	2.375	1 7/8	1.5
50	60.3	47.63	0.680
2 1/2	2.875	2	2.0
65	73.0	50.8	0.907
3 O.D.	2.996	2	2.0
76.1	76.1	50.8	0.907
3	3.500	2 1/4	2.5
80	88.9	57.15	1.134
4	4.5	2 5/8	5.0
100	114.3	66.68	2.268
5 1/2 O.D.	5.500	2 7/8	7.0
139.7	139.7	73.03	3.175
5	5.563	2 7/8	7.5
125	141.3	73.03	3.402
6 1/2 O.D.	6.500	3 1/8	10.0
165.1	165.1	79.38	4.536
6	6.625	3 1/8	10.0
150	168.3	79.38	4.536
8	8.625	3 7/8	18.5
200	219.1	98.43	8.391
10	10.75	4 3/8	32.5
250	237.1	111.13	14.741
12	12.75	4 7/8	48.0
300	323.9	123.83	21.772

All 7052i fittings are cast ductile iron.



For Listings/Approval Details and Limitations, visit our website at www.anvilint.com or contact an Anvil® Sales Representative.

C - Cast malleable or ductile iron, all others are fabricated steel.

* 14"-24" Standard Radius 90° & 45° Elbows are 1 1/2".

Center to end dimensions and weights may differ from those shown in chart, contact an Anvil Representative for more information.

PROJECT INFORMATION

APPROVAL STAMP

Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	