

FIG. 7063

Tee w/ Threaded Branch




FIGURE 7063 TEE WITH THREADED BRANCH				
Nominal Size	O.D.	C to GE	C to TE	Approx. Wt. Ea.
<i>In./DN(mm)</i>	<i>In./mm</i>	<i>In./mm</i>	<i>In./mm</i>	<i>Lbs./Kg</i>
1 25	1.315 33.4	2¼ 57	2¼ 57	0.9 0.4
1¼ 32	1.660 42.2	2¾ 70	2¾ 70	1.4 0.6
1½ 40	1.900 48.3	2¾ 70	2¾ 70	1.7 0.8
2 50	2.375 60.3	3¼ 83	4¼ 108	2.9 1.3
2½ 65	2.875 73.0	3¾ 95	3¾ 95	4.7 2.1
3 80	3.500 88.9	4¼ 108	6 152	8.1 3.7
3½ 90	4.000 101.6	4½ 114	4½ 114	8.8 4.0
4 100	4.500 114.3	5 127	7¼ 184	13.5 6.1
5 125	5.563 140	5½ 140	5½ 140	16.7 7.6
6 150	6.625 168.3	6½ 165	6½ 165	25.6 11.6
8 200	8.625 219.1	7¾ 197	7¾ 197	45.0 20.4
10 250	10.750 273.1	9 229	9 229	73.0 33.1
12 300	12.750 323.9	10 254	10 254	98.0 44.5

C - Cast malleable or ductile iron, all others are fabricated steel.
Center to end dimensions and weights may differ from those shown in chart, contact an Anvil Representative for more information.
See Fitting Size chart on page 50 for O.D.



For Listings/Approval Details and Limitations,
visit our website at www.anvilintl.com or
contact an Anvil® Sales Representative.

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			