

FIG. 7074

Cap




FIGURE 7074 CAP			
Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1C	1.315	1 1/4	0.3
25	33.4	32	0.1
1 1/4 C	1.660	1 1/4	0.4
32	42.2	32	0.2
1 1/2 C	1.900	1 1/4	0.5
40	48.3	32	0.2
2 C	2.375	1	0.5
50	60.3	25	0.2
2 1/2 C	2.875	1	0.7
65	73.0	25	0.3
3 O.D. C	2.996	1	0.8
76.1	76.1	25	0.4
3 C	3.500	1	1.1
80	88.9	25	0.5
3 1/2 C	4.000	1	1.4
90	101.6	25	0.6
4 1/4 O.D. C	4.250	1 1/8	2.0
108.0	108.0	29	0.9
4 C	4.500	1 1/8	2.8
100	114.3	29	1.3
5 1/4 O.D. C	5.236	1 1/8	3.2
133.0	133.0	29	1.5
5 1/2 O.D. C	5.500	1 1/8	4.0
139.7	139.7	29	1.8
5 C	5.563	1 1/8	4.0
125	141.3	29	1.8
6 1/4 O.D. C	6.259	1 1/8	5.1
159.0	159.0	29	2.3
6 1/2 O.D. C	6.500	1 1/8	6.0
165.1	165.1	29	2.7
6 C	6.625	1 5/16	6.0
150	168.3	33	2.7
8 C	8.625	1 1/2	12.5
200	219.1	38	5.7
10 C	10.750	1 1/2	21.9
250	273.1	38	9.9
12 C	12.750	1 1/2	33.8
300	323.9	38	15.3
14*	14.000	8 1/2	40
350	355.6	216	18.1
16*	16.000	9	45
400	406.4	229	20.4
18*	18.000	10	58
450	457.2	254	26.3
20*	20.000	11	79
500	508.0	279	35.8
24*	24.000	12 1/2	100
600	609.6	318	45.4

* Machined Cap

C - Cast Malleable or Ductile Iron

FIG. 7075

Bull Plug




FIGURE 7075 BULL PLUG			
Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
2	2.375	4	2.5
50	60.3	102	1.1
2 1/2	2.875	5	3.1
65	73.0	127	1.4
3	3.500	6	4.4
80	88.9	152	2.0
4	4.500	7	7.4
100	114.3	178	3.4
5	5.563	*	*
125	141.3	*	*
6	6.625	10	18.5
150	168.3	254	8.4

* Contact an Anvil Representative for dimensions & weights.
This product is not UL/ULC Listed or FM Approved.

FIG. 7068

Cross




FIGURE 7068 CROSS			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	2 1/4	1.3
25	33.4	57	0.6
1 1/4	1.660	2 3/4	2.1
32	42.2	70	1.0
1 1/2	1.900	2 3/4	2.5
40	48.3	70	1.1
2	2.375	3 1/4	2.9
50	60.3	83	1.3
2 1/2	2.875	3 3/4	5.2
65	73.0	95	2.4
3	3.500	4 1/4	7.5
80	88.9	108	3.4
3 1/2	4.000	4 1/2	9.8
90	101.6	114	4.4
4	4.500	5	12.2
100	114.3	127	5.5
5	5.563	5 1/2	17.6
125	141.3	140	8.0
6	6.625	6 1/2	28.3
150	168.3	165	12.8
8	8.625	7 3/4	48.0
200	219.1	197	21.8
10	10.750	9	70.0
250	273.1	229	31.8
12	12.750	10	110
300	323.9	254	49.9
14	14.000	11	140
350	355.6	279	63.5
16	16.000	12	170
400	406.4	305	77.1
18	18.000	15 1/2	260
450	457.2	394	118
20	20.000	17 1/4	320
500	508.0	438	145
24	24.000	20	585
600	609.6	508	265



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

PROJECT INFORMATION

APPROVAL STAMP

Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	