## **CONCRETE INSERTS & ATTACHMENTS**




## Fig. 47


## **Concrete Single Lug Plate**

Size Range: 1/2" through 2" Material: Carbon steel Finish: Plain or Galvanized Service: Structural attachment to concrete ceiling lug is used in conjunction with Fig. 299 (see page 98) forged steel clevis and anchors of sufficient

strength to hold the desired load.

Ordering: Specify rod size, figure number, name and finish.





|   | -   |
|---|-----|
| n |     |
|   | 2 2 |
|   | 0   |

| FIG. 47: LOAD (LBS) • WEIGHT (LBS) • DIMENSIONS (IN) |               |        |   |   |    |   |  |                                      |              |   |                                      |     |                               |
|--|---------------|--------|---|---|----|---|--|--------------------------------------|--------------|---|--------------------------------------|-----|-------------------------------|
| Rod Size<br>A  | Max<br>Load ■ | Weight | J | В | C  | D | E                                      | F                                    | G            | H   | R                                    | Т   | U                             |
| 1/2  | 1,350         | 11.1   | 1 |   | 10 | 5 | 47/8                                   | 9/16                                 | 3/8          |   | 11/4                                 | 1⁄4 | 5⁄8                           |
| 5/8  | 2,160         | 14.6   |   |   |    |   | 4 78                                   |                                      | 1/           | <sup>1</sup> / <sub>2</sub> 1 <sup>1</sup> / <sub>2</sub> |                                      |     | 3⁄4                           |
| 3⁄4  | 3,230         | 14.8   |   |   |    |   | <b>4</b> <sup>13</sup> ⁄ <sub>16</sub> | <sup>11</sup> ⁄ <sub>16</sub>        | 72           |   |                                      | 3⁄8 | 7⁄8                           |
| 7/8  | 4,480         | 22.0   |   |   |    |   |  |                                      | 3/4          |   |                                      |     | 1                             |
| 1  | 5,900         | 31.9   |   | 8 |    |   | 5 <sup>3</sup> ⁄4                      | <sup>13</sup> / <sub>16</sub>        | 74           | 2   | <b>1</b> ½                           | 1/2 | 11/8                          |
| 1 <sup>1</sup> /4                                    | 9,500         | 43.8   | 2 |   | 12 | 6 | 5 <sup>11</sup> /16                    | <sup>15</sup> ⁄ <sub>16</sub>        | 1            | 3   | 2                                    | 5⁄8 | 13%                           |
| 1½   | 13,800        | 45.6   |   |   |    |   |  | <b>1</b> <sup>1</sup> / <sub>8</sub> |              |   | <b>2</b> <sup>1</sup> / <sub>2</sub> | 3⁄4 | 15%                           |
| 1 <sup>3</sup> ⁄4                                    | 18,600        | 55.7   |   |   |    |   | 5%                                     | 1¾                                   | <b>-1</b> 1/ |   |                                      |     | 11 %                          |
| 2  | 24,600        | 58.2   |   |   |    |   |  | 1%                                   | 11⁄4         | 4   | 3                                    |     | 2 <sup>1</sup> / <sub>4</sub> |

Based on the rod diameter only. Rating is subject to the conditions that the concrete and anchors used are of sufficient strength to hold the load.

| PROJECT INFORMATION | APPROVAL STAMP    |
|---------------------|-------------------|
| Project:            | Approved          |
| Address:            | Approved as noted |
| Contractor:         | 🗋 Not approved    |
| Engineer:           | Remarks:          |
| Submittal Date:     |                   |
| Notes 1:            |                   |
| Notes 2:            |                   |
| PH-11.11            |                   |