## **BEAM CLAMPS**



## Fig. 14

## Adjustable Side Beam Clamp

Size Range: <sup>3</sup>/<sub>8</sub>" through <sup>5</sup>/<sub>8</sub>" Material: Carbon steel Finish: Plain or Galvanized Service: Recommended for supporting pipe from the bottom flange of beam Approvals: Complies with Federal Specification A-A-1192A (Type 27)

**Approvals:** Complies with Federal Specification A-A-1192A (Type 27) *WW-H-171-E (Type 54)*, ANSI/MSS SP-69 and MSS SP-58 (Type 27). **Ordering:** Specify rod size, figure number, name and finish.






FIG. 14: LOAD (LBS) • WEIGHT (LBS) • DIMENSIONS (IN)						
Rod Size A	Max Load	Hole Size A	Adjustment Beam Width		Weight	
			Min.	Max.		
3⁄8	300	<sup>7</sup> ⁄16	31/2	8	1.19	
1/2	700	<sup>9</sup> ⁄16			1.67	
5⁄8	1,000	11/16			2.23	

PROJECT INFORMATION	APPROVAL STAMP	
Project:	Approved	
Address:	Approved as noted	
Contractor:	🗋 Not approved	
Engineer:	Remarks:	
Submittal Date:		
Notes 1:		
Notes 2:		
PH-11.11		