
a xylem brand

SUBMITTAL

JOB:	REPRESENTATIVE:	
UNIT TAG:	ORDER NO.	DATE:
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:



Snap Zone Valve

DESCRIPTION

The B&G Snap Zone Valve is an on/off zone valve Maximum Operating Temperature: 212°F (100°C) for residential and light commercial HVAC applications. The valve opens and closes based upon the voltages applied to the actuator. Use the Minimum Ambient Temperature: 32°F (0°C) B&G Snap Zone Valves to speed installation time Maximum Operating Pressure: 240 PSI and reduce callback times to customers. The Maximum Differential Closeoff: 60 PSI actuator can be installed or removed at any angle on Open/Close Time: 3 min the adapter ring. The compact design and versatility Electrical Rating: 24V 60Hz in the actuator mounting position allows for easy installation in difficult positions.

Model Number Naming Convention

SZV	Snap Zone Valve				
050	Body Size				
	050 = 0.500"				
	075 = 0.750"				
	100 = 1.000"				
N	Connection Type				
	S = Sweat Body				
	N = FNPT Threaded				
4W	Actuator Type				
	4W = 4 Wire				
E	End Switch				
	E = Endswitch				


OPERATING DATA

Minimum Operating Temperature: 32°F (0°C) Maximum Ambient Temperature: 122°F (50°C)

Power Consumption: 1.8W, 75mA (6 Zone Valves per 40VA)

End Switch Rating: 1.0A @ 24VAC Glycol Compatibility: 50/50 mix

Wiring Diagram



MATERIALS OF CONSTRUCTION

Body: Forged Brass Bonnet/Packing Box: Brass

Plunger Assembly: Brass, EPDM Seals

Stem: Stainless Steel Union Nuts: Brass Tailpieces: Brass O-Rings: EPDM

Actuator: Polyamide Housing

Cable: PVC

Cv Ratings

ov mannige			
SIZE	1/2"	3/4"	1"
Cv	1.8	2.8	2.8

- 1. Thermostat
- 2. Brown
- 3. Blue 4. Black
- 5. Gray
- 6. 24V maximum, 3A ohm resistive load, 1A inductive load

SPECIFICATIONS

Model Number Part Number		Description	DIMENSIONS IN INCHES (mm)			Shipping Weight, Lbs.	
Model Number	Part Number	Description	D	X	Υ	Z	(kg.)
SZV-050S-4WE	109500	1/2" SWT Zone Valve, 4 Wire	1.59 (40.3)	3.48 (88.5)	3.55 (90.2)	4.24 (107.7)	1.4 (0.6)
SZV-075S-4WE	109501	3/4" SWT Zone Valve, 4 Wire	2.02 (51.3)	4.28 (108.7)	3.55 (90.2)	4.42 (112.5)	1.4 (0.6)
SZV-100S-4WE	109502	1" SWT Zone Valve, 4 Wire	2.24 (56.9)	4.28 (108.7)	3.55 (90.2)	4.52 (114.9)	1.4 (0.6)
SZV-050N-4WE	109506	1/2" NPT Zone Valve, 4 Wire	1.59 (40.3)	3.58 (91.0)	3.55 (90.2)	4.24 (107.7)	1.4 (0.6)
SZV-075N-4WE	109507	3/4" NPT Zone Valve, 4 Wire	2.02 (51.3)	4.18 (106.1)	3.55 (90.2)	4.42 (112.5)	1.4 (0.6)
SZV-100N-4WE	109508	1" NPT Zone Valve, 4 Wire	2.24 (56.9)	4.44 (112.7)	3.55 (90.2)	4.52 (114.9)	1.4 (0.6)

Xvlem Inc. 8200 N. Austin Avenue Morton Grove, IL 60053 Phone: (847)966-3700 www.xyleminc.com/brands/bellgossett

