

MATERIAL SAFETY DATA SHEET

MSDS 0272

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

		HMIS CODES	
PRODUCT NAME	Grime-Solv	Health	2
		Flammability	0
		Reactivity	0
PRODUCT CODES	88436	PPI	B
CHEMICAL FAMILY	Organic		
USE	Cleaner & Degreaser		
MANUFACTURER'S NAME	The RectorSeal Corporation	EMERGENCY TELEPHONE NO.	
	2601 Spenwick Drive	Chemtrec 24 Hours	
	Houston, Texas 77055 USA	(800)424-9300 USA	
		(703)527-3887 International	
DATE OF VALIDATION	October 5, 2012	TECHNICAL SERVICE TELEPHONE NO.	
		(800)231-3345 or (713)263-8001	
DATE OF PREPARATION	October 5, 2012		

Section 2 -- HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Carcinogen, Target Organ Effect, Harmful by ingestion., Irritant

Target Organs

Liver, pancreas, Blood, Central nervous system, Heart, Kidney

GHS Classification

Acute toxicity, Oral (Category 5)

Skin irritation (Category 2)

Eye irritation (Category 2B)

Carcinogenicity (Category 2)

GHS Label elements, including precautionary statements

Pictogram: Chronic Health Hazard, Irritant

Signal Word: Warning

Hazard statement(s)

H302 - Harmful if swallowed.

H315 + H320 - Causes skin and eye irritation.

H351 - Suspected of causing cancer.

H401 - Toxic to aquatic life.

Precautionary statement(s)

P281 - Use personal protective equipment as required.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SUMMARY OF ACUTE HAZARDS

Repeated inhalation may cause dizziness, nausea and CNS effects. May cause severe eye and skin irritation.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

EYE CONTACT

Contact with eyes may cause severe irritation.

SKIN CONTACT

Irritation and drying.

INGESTION

May cause irritation of the digestive tract. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

SUMMARY OF CHRONIC HAZARDS

Skin irritation, contact dermatitis, and defatting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT: Tetrachloroethylene

PERCENTAGE BY WEIGHT: 40-46

CAS NUMBER: 127-18-4

EC# : 204-825-9

INGREDIENT: Methylene Chloride

PERCENTAGE BY WEIGHT: 40-46

CAS NUMBER: 75-09-2

EC# : 200-838-9

INGREDIENT: Glycol Butyl Ether

PERCENTAGE BY WEIGHT: 1-3

CAS NUMBER: 111-76-2

EC# : 203-905-0

INGREDIENT: Isobutanol-2-amine

PERCENTAGE BY WEIGHT: 1-3

CAS NUMBER: 124-68-5

EC# : 204-709-8

Section 4 -- FIRST AID MEASURES

If INHALED:	If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
If on SKIN:	Immediately wash with soap and water. Remove and wash any contaminated clothing.
If in EYES:	Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.
If SWALLOWED:	If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Section 5 -- FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Foam, dry chemical, CO₂, or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and full body protective clothing. Hazardous decomposition products possible (see Section 10). Evacuate area. Dike area as run-off may create additional environmental contamination.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Aerosol cans are under pressure - exposure to temperatures above 120F can cause bursting or "rocketing" of cans.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use absorbent materials to prevent footing hazard and to contain. Ventilate area with forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Shake well before using. Keep away from heat and open flames. Prolonged exposure to direct sunshine or storage above 120 F may cause can to burst. Do not puncture or incinerate can. OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT UNITS

Tetrachloroethylene

ACGIH TLV	50 ppm
OSHA PEL	25 ppm

Methylene Chloride

ACGIH TLV	50 ppm
OSHA PEL	25 ppm
OSHA STEL	125 ppm

Glycol Butyl Ether

ACGIH TLV	25 ppm
OSHA PEL	25 ppm

Isobutanol-2-amine

ACGIH TLV	N/D
OSHA PEL	N/D

Nitrous Oxide

ACGIH TLV	50 ppm
OSHA PEL	N/D

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirator.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion proof

MECHANICAL (GENERAL): Acceptable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical resistant coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 104 F (40 C) @ 760mm Hg
SPECIFIC GRAVITY (H2O = 1): 1.32
VAPOR PRESSURE (mm Hg): 350 mm HG @ 20 C
MELTING POINT: N/A
VAPOR DENSITY (AIR = 1): 2.9
EVAPORATION RATE (ETHYL ACETATE = 1): >1
APPEARANCE/ODOR: Clear Liquid / Mild Odor
SOLUBILITY IN WATER: Insoluble
AEROSOL FLAME EXTENSION: Negative
FLASH POINT: None
LOWER EXPLOSION LIMIT: N/D
UPPER EXPLOSION LIMIT: N/D
VOLATILE ORGANIC COMPOUNDS (VOC) Content
(Theoretical Percentage By Weight): >6% or (60 g/L)

Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Do not store in temperatures above 120 F.
INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers, acids and bases.
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO, and fragmented hydrocarbons.
HAZARDOUS POLYMERIZATION: Will not occur.

Section 11 -- TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Methylene chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure.
IARC: 2A - Group 2A: Probably carcinogenic to humans (Tetrachloroethylene)
NTP: Reasonably anticipated to be a human carcinogen (Tetrachloroethylene)

TOXICOLOGY DATA

Ingredient Name

Tetrachloroethylene

Oral-Rat LD50: 2629 mg/kg
Inhalation-Rat LC50: 34,200 mg/m³/8H

Methylene Chloride

Oral-Rat LD50: 1600 mg/kg
Inhalation-Rat LC50: 88,000 mg/m³/30M

Glycol Butyl Ether

Oral-Rat LD50: 470 mg/kg
Inhalation-Rat LC50: 2900 mg/m³

Isobutanol-2-amine

Oral-Rat LD50: 2900 mg/kg
Inhalation-Rat LC50: N/D

Nitrous Oxide

Oral-Rat LD50:N/D

Inhalation-Rat LC50:160 mg/m3/6H

Section 12 -- Ecological Information

ECOLOGICAL DATA

Ingredient Name

Tetrachloroethylene

Food Chain Concentration Potential None

WATERFOWL TOXICITY N/A

BOD None

AQUATIC TOXICITY N/A

Methylene Chloride

Food Chain Concentration Potential None

WATERFOWL TOXICITY N/A

BOD N/A

AQUATIC TOXICITY N/A

Glycol Butyl Ether

Food Chain Concentration Potential None

WATERFOWL TOXICITY N/A

BOD 26%

AQUATIC TOXICITY 1000 ppm/24 hr/brine shrimp/TLm

Isobutanol-2-amine

Food Chain Concentration Potential N/A

WATERFOWL TOXICITY N/A

BOD N/A

AQUATIC TOXICITY N/A

Nitrous Oxide

Food Chain Concentration Potential None

WATERFOWL TOXICITY None

BOD None

AQUATIC TOXICITY None

Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Aerosols

Disposal Method: Empty containers can be disposed of in trash. Full containers should be depressurized to separate liquid phase. The liquid phase is considered a U210 and U080 hazardous waste and should be incinerated. Dispose of all liquid waste in accordance with all local, state and federal regulations.

Section 14 -- TRANSPORTATION INFORMATION

DOT: UN1950, Aerosols, Class 2.2, ERG#126

OCEAN (IMDG): UN1950, Aerosols, Class 2.2, LTD-QTY, EMS-No: F-A, S-A

AIR (IATA): UN1950, Aerosols, Class 2.2, ERG#126

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA

Ingredient Name

Tetrachloroethylene

SARA 313

Yes

	TSCA Inventory	Yes
	CERCLA RQ	100 lbs.
	RCRA Code	U210
Methylene Chloride		
	SARA 313	Yes
	TSCA Inventory	Yes
	CERCLA RQ	1000 lbs.
	RCRA Code	U080
Glycol Butyl Ether		
	SARA 313	No
	TSCA Inventory	Yes
	CERCLA RQ	N/A
	RCRA Code	N/A
Isobutanol-2-amine		
	SARA 313	No
	TSCA Inventory	Yes
	CERCLA RQ	N/A
	RCRA Code	N/A
Nitrous Oxide		
	SARA 313	No
	TSCA Inventory	Yes
	CERCLA RQ	N/A
	RCRA Code	N/A

CALIFORNIA PROPOSITION 65

This product contains tetrachloroethylene and methylene chloride known to the state of California to cause cancer and/or birth defects or reproductive harm.

Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001