Revision Number: 003.0

Issue date: 08/15/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **TECHNOMELT PS 8845 known as TECHNOMELT 86-8845**

IDH number: 884580

Product type: Hotmelt adhesive

Restriction of Use: None identified

Region: United States

Company address:
Henkel Corporation
One Henkel Way
Rocky Hill, Connecticut 06067

Contact information:
Telephone: (860) 571-5100
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
WARNING:	MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS. STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR FLAMMABLE VAPORS MAY CAUSE IGNITION. VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention: Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Not prescribed

Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Pentaerythritol ester of rosin	Proprietary	30 - 60
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5 - 10

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.

Skin contact: No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.

Ingestion: Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use extinguishing measures appropriate to local circumstances and the surrounding environment. Carbon dioxide, foam, powder

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Acrid smoke and fumes. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Prevent contamination of soil and water.

Clean-up methods: Wear appropriate protective equipment and clothing during clean-up. If product is molten at time of spill, allow it to polymerize before scraping up. If product is solid at time of spill, sweep up. Avoid creating static electricity while sweeping as static discharge may occur. Store picked up product for either reuse or disposal. Follow all local, state, federal and provincial regulations for disposal.

7. HANDLING AND STORAGE

Handling: Wear suitable protective clothing, safety glasses and gloves. Avoid skin and eye contact. Avoid breathing vapors or mists of this product. Keep container closed.

Storage: For safe storage, store between 0 °C (32°F) and 38 °C (100.4 °F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Pentaerythritol ester of rosin	None	None	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None

Engineering controls: Heat only in areas with appropriate exhaust ventilation. Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection: Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses. Safety goggles or safety glasses with side shields.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid
Color: Straw, Light
Odor: Resinous
Odor threshold: Not available.
pH: Not available.
Vapor pressure: Not determined
Boiling point/range: > 220 °C (> 428°F)
Melting point/ range: > 110 °C (> 230°F)
Specific gravity: 0.98
Vapor density: Not available.
Flash point: > 220 °C (> 428°F) ASTM D-93
Flammable/Explosive limits - lower: Not applicable
Flammable/Explosive limits - upper: Not applicable
Autoignition temperature: Not applicable
Evaporation rate: Not applicable
Solubility in water: Insoluble
Partition coefficient (n-octanol/water): Not available.
VOC content: Negligible
Viscosity: 14,000 - 21,000 cp
Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Smoke. Oxides of carbon.

Incompatible materials: Avoid heating above 400ºF.

Reactivity: Not available.

Conditions to avoid: Prolonged heating at temperatures above 200 °C.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Molten adhesive., Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.

Skin contact: Solid adhesive has no hazards. Molten adhesive may cause severe burns.

Eye contact: Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical irritation if dusts are generated.

Ingestion: Not expected to be harmful by ingestion.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Pentaerythritol ester of rosin	None	Irritant
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Pentaerythritol ester of rosin	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None
Exceptions: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis
CERCLA/SARA Section 311/312: Immediate Health
CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: J. Boryszewski, Regulatory Affairs

Issue date: 08/15/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates (“Henkel”) does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user’s responsibility to determine the suitability of Henkel’s products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel’s products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel’s products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.