Material Safety Data Sheet



Revision Number: 002.2 Issue date: 04/26/2013

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-GP 4141 CORROSION IDH number: 879525

INHIBITOR known as P3 PREVOX 4141

Product type: Rust preventor

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 248.583.9300

32100 Stephenson Highway MEDICAL EMERGENCY Phone: Poison Control Center Madison Heights, MI 48071 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:LiquidHEALTH:1Color:brownFLAMMABILITY:2Odor:characteristicPHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

CAUTION: COMBUSTIBLE!

CAUSES EYE AND SKIN IRRITATION. ASPIRATION HAZARD IF SWALLOWED.

MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Excessive inhalation of this material causes headache, dizziness, nausea and incoordination. Repeated and prolonged overexposure to oil mists may result in droplet deposition, oil

granuloma formation, inflammation and increased incidence of infection.

Skin contact: This product may cause irritation to the skin. Prolonged or repeated skin contact may result in

redness, burning sensation or dermatitis. Prolonged or repeated contact with this product may

dry and/or defat the skin.

Eye contact: This product is irritating to the eyes.

Ingestion: May cause dizziness, incoordination, headache, nausea, and vomiting. Small amounts of this

product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Existing conditions aggravated by

exposure:

Eye, skin and respiratory disorders.

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Petroleum hydrocarbon solvent	Proprietary	60 - 100
Additive	Proprietary	5 - 10

IDH number: 879525 Product name: BONDERITE L-GP 4141 CORROSION INHIBITOR known as P3 PREVOX 4141 Page 1 of 5

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). If

symptoms develop and persist, get medical attention.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

Ingestion: Seek medical advice. DO NOT induce vomiting unless directed to do so by

medical personnel.

Notes to physician: This material, if aspirated into the lungs, may cause chemical pneumonitis;

treat the affected person appropriately.

5. FIRE FIGHTING MEASURES

Flash point: 62 °C (143.6 °F) Pensky Martens closed cup

Autoignition temperature: Not determined

Flammable/Explosive limits - lower: Not determined

Flammable/Explosive limits - upper: Not determined

IDH number: 879525

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Water may be an

ineffective extinguishing medium.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: Fire and explosion hazards are moderate when this product is exposed to heat

or flame. Vapors are heavier than air and may travel to ignition sources and

flash back.

Hazardous combustion products: Irritating and toxic gases or fumes may be released during a fire. Upon

decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear suitable protective

clothing, gloves and eye/face protection. Eliminate ignition sources including

sources of electrical, static or frictional sparks.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. Do not take internally. For industrial use only. Keep away from

heat, spark and flame.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty

containers.

For safe storage, store at or below 60.0 °C (140°F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Petroleum hydrocarbon solvent	None	None	None	None
Additive	None	None	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If mist is generated (heating, spraying) and engineering controls are not

sufficient, wear approved organic vapor respirator suitable for oil mist.

Eye/face protection: Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: brown

Odor: characteristic
Odor threshold: Not available.
pH: Not available.

Vapor pressure:0.7000000 mbar (20.0 °C (68°F)) calculatedBoiling point/range:192 °C (377.6 °F) Supplier's method

Melting point/ range:

Specific gravity:

Not determined

0.808 at 22 °C (71.6 °F)

Vapor density: Not applicable

Flash point: 62 °C (143.6 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not determined

Not available.

Not determined

Not determined

Not available.

IDH number: 879525

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions:None under normal processing.

Hazardous decomposition products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

Incompatible materials: This product may react with strong oxidizing agents. This product reacts with

acids.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Petroleum hydrocarbon solvent	No	No	No
Additive	No	No	No

Hazardous components	Health Effects/Target Organs
Petroleum hydrocarbon solvent	Irritant, Lung
Additive	No Data

12. ECOLOGICAL INFORMATION

Ecological information:No data available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Wastes must be tested using methods described in 40 CFR Part 261 to

determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Petroleum distillates)

Hazard class or division: Combustible Liquid

Identification number: NA 1993
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None

Identification number:NonePacking group:None

15. REGULATORY INFORMATION

United States Regulatory Information

IDH number: 879525

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Fire

CERCLA/SARA 313: None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Product name: BONDERITE L-GP 4141 CORROSION INHIBITOR known as P3 PREVOX 4141

Page 4 of 5

Canada Regulatory Information

IDH number: 879525

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: B.3, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: Updated Contact Information in Section 1.

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.