



Revision Number: 003.0

Issue date: 07/21/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>BONDERITE S-FN 6767 CORROSION INHIBITOR known as P3 PREVOX 6767</b>	<b>IDH number:</b>	595793
<b>Product type:</b>	Lubricant	<b>Region:</b>	United States
<b>Restriction of Use:</b>	None identified	<b>Contact information:</b>	
<b>Company address:</b>	Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com		
Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067			

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves.
<b>Response:</b>	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

6 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

IDH number: 595793

Product name: BONDERITE S-FN 6767 CORROSION INHIBITOR known as P3 PREVOX 6767

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	60 - 100
Amine soap	Proprietary	10 - 30
Barium sulfonate	61790-48-5	1 - 5
Barium compound	513-77-9	1 - 5
Diethanolamine	111-42-2	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
<b>Skin contact:</b>	Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.
<b>Ingestion:</b>	Get immediate medical attention. Do not induce vomiting.
<b>Symptoms:</b>	See Section 11.
<b>Notes to physician:</b>	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide. In case of fire, keep containers cool with water spray.
<b>Special firefighting procedures:</b>	Wear full protective clothing. Wear self-contained breathing apparatus.
<b>Unusual fire or explosion hazards:</b>	This product is combustible at high temperatures.
<b>Hazardous combustion products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up.
<b>Clean-up methods:</b>	Absorb spill with inert material. Shovel material into appropriate container for disposal. Ventilate area. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

**Handling:**

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Do not take internally. For industrial use only. Use only with adequate ventilation. Launder work clothes frequently.

**Storage:**

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Manufacturer recommends storing above 4.4 °C (40 °F). If stored outside of this range, mix well before using. Do not pressurize, cut, heat or weld containers. Empty product containers may contain product residue. Do not reuse empty containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated light naphthenic	Included in the regulation but with no data values. See regulation for further details Exposure by all routes should be carefully controlled to levels as low as possible.	5 mg/m3 TWA mist 10 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Amine soap	None	None	None	None
Barium sulfonate	0.5 mg/m3 TWA (as Ba)	0.5 mg/m3 PEL (as Ba)	None	None
Barium compound	0.5 mg/m3 TWA (as Ba)	0.5 mg/m3 PEL (as Ba)	None	None
Diethanolamine	1 mg/m3 TWA Inhalable fraction and vapor. (SKIN) Inhalable fraction and vapor.	None	None	None

**Engineering controls:**

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

**Respiratory protection:**

When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed. If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

**Eye/face protection:**

Wear chemical goggles; face shield (if splashing is possible).

**Skin protection:**

Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Liquid

**Color:**

amber

**Odor:**

Mineral oil

**Odor threshold:**

Not available.

**pH:**

9.0 - 9.5

Vapor pressure:	Not determined
Boiling point/range:	> 400 °F (> 204.4 °C)
Melting point/ range:	Not available.
Specific gravity:	0.91 - 0.94 at 15.6 °C (60.08 °F)
Vapor density:	Not determined
Flash point:	> 280 °F (> 137.78 °C)
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Appreciable
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Not determined
Viscosity:	Not available.
Decomposition temperature:	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable at normal conditions.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
<b>Incompatible materials:</b>	Strong oxidizing agents. Strong acids.
<b>Reactivity:</b>	Nitrites may react with organic amines to form nitrosamines which can cause cancer.
<b>Conditions to avoid:</b>	Avoid excessive heat and ignition sources.

## 11. TOXICOLOGICAL INFORMATION

<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes
-------------------------------------	------------------------

### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

**Skin contact:** This product is irritating to the skin. This product may cause an allergic skin reaction. A component in this product may be absorbed through the skin in harmful amounts.

**Eye contact:** Contact with this product may cause severe eye damage.

**Ingestion:** Ingestion of this product may cause nausea, vomiting and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated light naphthenic	None	Irritant
Amine soap	None	Irritant, Allergen, Corrosive, Skin, Liver, Kidney, Nervous System, Lung, Heart, Reproductive, Thyroid, Pancreas, Blood, Adrenals
Barium sulfonate	None	No Records
Barium compound	Oral LD50 (RAT) = 418 mg/kg Oral LD50 (RAT) = 630 - 750 mg/kg Oral LD50 ( ) = 1,480 mg/kg	Reproductive, Gastrointestinal, Kidney, Nervous System, Cardiac, Lung, Blood, Metabolic
Diethanolamine	Oral LD50 (RAT) = 710 mg/kg Oral LD50 (RAT) = 1.82 g/kg	Allergen, Blood, Brain, Central nervous system, Corrosive, Heart, Irritant, Kidney, Liver, Respiratory, Spleen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated light naphthenic	Known To Be Human Carcinogen.	Group 1	No
Amine soap	No	No	No
Barium sulfonate	No	No	No
Barium compound	No	No	No
Diethanolamine	No	Group 2B	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** RQ, Environmentally hazardous substances, liquid, n.o.s.  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III  
**DOT Hazardous Substance(s):** Diethanolamine

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Environmentally hazardous substance, liquid, n.o.s.  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III

**15. REGULATORY INFORMATION****United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Barium sulfonate (CAS# 61790-48-5). Barium compound (CAS# 513-77-9). Diethanolamine (CAS# 111-42-2) 100 lbs. (45.4 kg)  
**CERCLA Reportable quantity:**  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information**

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Jennifer Mckay, Regulatory Affairs Specialist

**Issue date:** 07/21/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.