

Revision Number: 005.1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type:

BONDERITE L-GP SN 400C CORROSION INHIBITOR known as P3 PREVOX SN-400C Industrial Metal Working Agents IDH number:

595510

Company address:

Henkel Corporation 32100 Stephenson Highway Madison Heights, MI 48071 Region:United StatesContact information:Telephone: 248.583.9300MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW HMIS:			
Color: Br	HEALTH: 2 own FLAMMABILITY: 1 etroleum PHYSICAL HAZARD: 0 Personal Protection: See MSDS Section 8		
WARNING:	CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.		
Relevant routes of exposure:	Skin, Inhalation, Eyes		
Potential Health Effects			
Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination		
Skin contact:	Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis. Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals.		
Eye contact: Ingestion:	Severe eye irritation. Ingestion of this product may cause nausea, vomiting and diarrhea. May cause dizziness, incoordination, headache, nausea, and vomiting. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.		
Existing conditions aggravate exposure:	d by Pre-existing skin, eye and respiratory allergies.		
	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).		

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 60	
Methylpentanediol-2,4, 2-	107-41-5	10 - 30	
Sodium sulfonate	Proprietary	5 - 10	
Sodium sulfonate	Proprietary	5 - 10	
Substituted Ether	Proprietary	1 - 5	
Barium sulfonate	61790-48-5	1 - 5	
Polyamide resin	Proprietary	1 - 5	

Product name: BONDERITE L-GP SN 400C CORROSION INHIBITOR known as P3 PREVOX SN-400C

Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fres air. Seek medical attention if symptoms develop or persist.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with eyes, rinse immediately with plenty of water and seel medical advice.
Ingestion:	Immediate medical treatment necessary. DO NOT induce vomiting unless directed to do so by medical personnel.
Notes to physician:	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.
5. I	FIRE FIGHTING MEASURES
Flash point:	100 °C (212°F) None
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Extinguishing media:	Use media appropriate for surrounding material.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	This product is combustible at high temperatures.
Hazardous combustion products:	Irritating and toxic gases or fumes may be released during a fire.
6 100	DENTAL RELEASE MEASURES

	personnel.	
Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear suitable protective clothing, gloves and eye/face protection.	
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.	

7. HANDLING AND STORAGE

 Handling:
 Avoid contact with eyes, skin and clothing. Do not take internally. For industrial use only.

 Storage:
 Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Manufacturer recommends storing above 4.4 °C (40 °F). Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Product name: BONDERITE L-GP SN 400C CORROSION INHIBITOR known as P3 PREVOX SN-400C

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist 5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) TWA 5 mg/m3 TWA Mist.	None	None
Methylpentanediol-2,4, 2-	25 ppm Ceiling	None	None	None
Sodium sulfonate	None	None	None	None
Sodium sulfonate	None	None	None	None
Substituted Ether	None	None	None	None
Barium sulfonate	0.5 mg/m3 TWA (as Ba)	0.5 mg/m3 TWA (as Ba)	None	None
Polyamide resin	None	None	None	None

Engineering controls:

Respiratory protection:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Skin protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state: Color: Odor: Odor threshold: pH: . Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: **Evaporation rate:** Solubility in water: Partition coefficient (n-octanol/water): **VOC content:**
- Liquid Brown Petroleum Not available 7.00 Not determined 215 °F (101.7 °C) None Not available 0.942 at 20 °C (68°F) Not determined 100 °C (212°F) None Not applicable Not applicable Not available Not applicable Complete Not available Not applicable

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	This product may react with strong oxidizing agents.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

Product name: BONDERITE L-GP SN 400C CORROSION INHIBITOR known as P3 PREVOX SN-400C

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Methylpentanediol-2,4, 2-	No	No	No
Sodium sulfonate	No	No	No
Sodium sulfonate	No	No	No
Substituted Ether	No	No	No
Barium sulfonate	No	No	No
Polyamide resin	No	No	No

Hazardous components	Health Effects/Target Organs
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant
Methylpentanediol-2,4, 2-	Irritant, Central nervous system
Sodium sulfonate	No Records
Sodium sulfonate	No Data
Substituted Ether	Allergen, Irritant, Kidney
Barium sulfonate	No Records
Polyamide resin	Allergen, Irritant

12. ECOLOGICAL INFORMATION

Ecological information:

No data available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA.

14. TRANSPORT INFORMATION

Not regulated None None None

U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Not regulated

Proper shipping name:	Not re
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.	
TSCA 12(b) Export Notification:	None above reporting de minimus	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Barium sulfonate (CAS# 61790-48-5).	
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.	
Canada Regulatory Information		
CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details. WHMIS hazard class: D.2.B		
	U.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format., Updated composition in Section 3.

Prepared by: Jennifer Mckay, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.