Safety Data Sheet



Revision Number: 002.0

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product type:

Restriction of Use:

Company address:

Henkel Corporation

One Henkel Way

BONDERITE S-MA 2247 PAINT STRIPPER known as P3 TACKY OVEN **COATING 2247** Strippable protective paint coating None identified Rocky Hill, Connecticut 06067

Region: **United States** Contact information: Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT ENERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

592955

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
WARNING:	FLAMMABLE LIQUID AND VAPOR.
	CAUSES SKIN IRRITATION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)

Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools.
	Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray.
	Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection.
Response:	If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Product name: BONDERITE S-MA 2247 PAINT STRIPPER known as P3 TACKY OVEN CO 2247 Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Aliphatic petroleum solvent	Proprietary	60 - 100

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	If inhaled, immediately remove the affected person to fresh air. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.	
Skin contact:	For skin contact flush with large amounts of water. If symptoms develop and persist, get medical attention.	
Eye contact:	Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.	
Ingestion:	Get immediate medical attention. Do not induce vomiting.	
Symptoms:	See Section 11.	
5.	FIRE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.	
Unusual fire or explosion hazards:	Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Do not pressurize, cut, heat c weld containers. Empty product containers may contain product residue. D not reuse empty containers.	
Hazardous combustion products:	Irritating and toxic gases or fumes may be released during a fire.	
6. ACC	IDENTAL RELEASE MEASURES	

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear suitable protective clothing, gloves and eye/face protection. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations. Ventilate area.

7. HANDLING AND STORAGE

Handling:

Storage:

Avoid contact with eyes, skin and clothing. Do not take internally. For industrial use only. Provide adequate ventilation.

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Aliphatic petroleum solvent	100 ppm TWA	500 ppm (2,900 mg/m3) TWA	None	None
Engineering controls:	Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.			
Respiratory protection:	If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.			
Eye/face protection:	Wear chemical goggles; face shield (if splashing is possible).			
Skin protection:	Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boot are recommended.			

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Liquid Colorless Petroleum Not available. Not applicable 1 mm hg > 159 °Č (> 318.2 °F) Not determined 0.80 - 0.81 at 27 °C (80.6 °F) > 1 40.6 °C (105.08 °F) 7% 1% Not applicable Not available. Negligible Not determined 563 g/I EPA Method 24 Not available. Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Thermal decomposition can lead to release of irritating gases and vapors.
Incompatible materials:	This product may react with strong acids, bases and oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, spark and flame.
11. TOXICOLOGICAL INFORMATION	

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.Skin contact:Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.Eye contact:This product is irritating to the eyes.Ingestion:May cause temporary irritation of the throat, stomach, and gastrointestinal tract.

Hazardous Component(s)	LD50s and LC50	LD50s and LC50s		and Delayed Health Effects
Aliphatic petroleum solvent	None	None		nervous system, Irritant
Hazardous Component(s)	NTP Carcinogen	IARC Ca	rcinogen	OSHA Carcinogen (Specifically Regulated)
Aliphatic petroleum solvent	No	N	lo	No

12. ECOLOGICAL INFORMATION

Ecological information:

Hazardous waste number:

No data available.

13. DISPOSAL CONSIDERATIONS

 Information provided is for unused product only.

 Recommended method of disposal:
 Follow all local, state, federal and provincial regulations for disposal.

If discarded, this product is considered a RCRA ignitable waste, D001. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

.S. Department of Transportation Ground (49 CFR)			
Proper shipping name:	Combustible liquid, n.o.s. (Solvent naphtha)		
Hazard class or division:	Combustible Liquid		
Identification number:	NA 1993		
Packing group:	111		

IDH number: 592955

υ.

International Air Transportation (ICAO/IATA) Proper shipping name: Hazard class or division: Identification number: Packing group:	Petroleum products, n.o.s. 3 UN 1268 III
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	PETROLEUM PRODUCTS, N.O.S. 3 UN 1268 III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis Immediate Health, Fire None above reporting de minimis
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: John DiCerbo, Sr. Regulatory Affairs Specialist

Issue date: 08/15/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.