



Revision Number: 002.0

Issue date: 01/08/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: TECHNOMELT PA 2192B known as Macromelt 2192 B
Product type: Hotmelt adhesive
Company address: Henkel Corporation
10 FINDERNE AVENUE
BRIDGEWATER, NEW JERSEY 08807

IDH number: 1396374
Region: United States
Contact information:
Customer Service: 1-888-480-6889
MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC
1-800-424-9300 (toll free) or 1-703-527-3887
Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Physical state: solid
Color: Amber
Odor: characteristic

HMIS:
HEALTH: 2
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

CAUTION: ADHESIVE VAPORS MAY CAUSE SLIGHT IRRITATION OF THE EYES, SKIN OR RESPIRATORY SYSTEM.
MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Dusts from solid adhesive may cause irritation. Continuous breathing of vapors above molten adhesive may irritate mucous membranes.

Skin contact: Solid adhesive has no hazards. Molten adhesive may cause severe burns.

Eye contact: Molten adhesive in eyes will cause severe and permanent damage. Can cause mechanical irritation if dusts are generated.

Ingestion: Not expected to be harmful by ingestion. Not expected under normal conditions of use.

Existing conditions aggravated by exposure: None known

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
None	None	None

4. FIRST AID MEASURES

Inhalation: If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

Skin contact:

Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn. Cover affected areas with clean sheeting or gauze and seek immediate medical attention.

Eye contact:

If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.

Ingestion:

If symptoms develop and persist, get medical attention. Ingestion of solid adhesive is not expected to be hazardous.

5. FIRE FIGHTING MEASURES

Flash point:

No flash point up to 200 °C

Autoignition temperature:

Not applicable

Flammable/Explosive limits - lower:

Not applicable

Flammable/Explosive limits - upper:

Not applicable

Extinguishing media:

Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA). Wear full protective clothing.

Unusual fire or explosion hazards:

None

Hazardous combustion products:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released. Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow material to contaminate ground water system. No special environmental precautions required.

Clean-up methods:

Sweep up spilled material. Avoid creating dust. Health injuries are not known or expected under normal use.

7. HANDLING AND STORAGE

Handling:

Follow suggested application temperature. Do not place wet or damp solid into melt tank. Avoid skin contact with molten resins.

Storage:

For safe storage, store at or below 38 °C (100.4 °F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls:

General room ventilation is usually adequate. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Respiratory protection:

No personal respiratory protective equipment normally required. Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate. Observe OSHA regulations for respiratory use (29 CFR 1910.134).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.

Skin protection:

Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	solid
Color:	Amber
Odor:	characteristic
Odor threshold:	Not available
pH:	Not applicable
Vapor pressure:	not applicable
Boiling point/range:	Not applicable
Melting point/ range:	167 - 177 °C (332.6 - 350.6 °F) (Softening Point)
Specific gravity:	1.0 - 1.1
Vapor density:	Not available
Flash point:	No flash point up to 200 °C
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	Not applicable
Solubility in water:	Not available
Partition coefficient (n-octanol/water):	Not available
VOC content:	0 g/l

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Thermal decomposition can lead to release of irritating gases and vapors.
Incompatible materials:	Oxidizing agents.
Conditions to avoid:	Avoid temperatures above 260°C (500°F).

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity:	LD50 > 5000 mg/kg body weight (rat)
------------------------------	-------------------------------------

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

Hazardous components	Health Effects/Target Organs
None	None

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: This product is not a RCRA hazardous waste when discarded. Processing, use, or contamination of this product may change the hazard classification and waste management options. Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: None
CERCLA/SARA 313: None above reporting de minimus
California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class: Not controlled

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Ed Waldynski, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.