



Revision Number: 001.0

Issue date: 01/08/2013

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** LOCTITE MOLY PASTE 12OZ AE EN  
**Product type:** Antiseize

**IDH number:** 1852755  
**Item number:** 1852755  
**Region:** United States

**Company address:**  
Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067

**Contact information:**  
Telephone: 860.571.5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkelna.com

**2. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

**Physical state:** Liquid  
**Color:** Black  
**Odor:** Solvent

**HMIS:**

**HEALTH:** \*1  
**FLAMMABILITY:** 3  
**PHYSICAL HAZARD:** 0  
**Personal Protection:** Not available.

**DANGER:** EXTREMELY FLAMMABLE.  
CONTENTS UNDER PRESSURE.  
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR INHALED.

**Relevant routes of exposure:** Lungs, Skin, Eyes

**Potential Health Effects**

**Inhalation:** Vapor overexposure may cause drowsiness. Prolonged or excessive inhalation may cause respiratory tract irritation.  
**Skin contact:** May be harmful if absorbed through skin. May cause skin irritation. May cause sensitization by skin contact.  
**Eye contact:** Direct spray or vapors will irritate and may harm eyes. Direct contact with liquid may cause corneal damage and visual impairment.  
**Ingestion:** Harmful if swallowed.

**Existing conditions aggravated by exposure:** Not available.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Molybdenum disulphide	1317-33-5	10 - 30
Propane/Isobutane	68476-86-8	10 - 30
Acetone	67-64-1	10 - 30
n-Heptane	142-82-5	10 - 30
Methyl acetate	79-20-9	10 - 30
Calcium dihydroxide	1305-62-0	1 - 5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1 - 5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	1 - 5

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	If symptoms develop and persist, get medical attention. Wash affected area immediately with soap and water.
<b>Eye contact:</b>	Get medical attention. Immediately flush eyes with plenty of water for at least 15 minutes.
<b>Ingestion:</b>	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Aspiration may cause pulmonary edema and pneumonitis. Get immediate medical attention.

### 5. FIRE FIGHTING MEASURES

<b>Flash point:</b>	< -17 °C (< 1.4 °F)
<b>Autoignition temperature:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
<b>Unusual fire or explosion hazards:</b>	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Do not puncture or incinerate pressurized containers.
<b>Hazardous combustion products:</b>	Oxides of carbon.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Eliminate ignition sources including sources of electrical, static or frictional sparks. Wipe up with adsorbent material (e.g. cloth, fleece). Rinse spill area with water. Store in a partly filled, closed container until disposal.

## 7. HANDLING AND STORAGE

**Handling:**

Keep away from heat, spark and flame. Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapor/spray.

**Storage:**

Keep in a cool, well ventilated area. Store away from heat, sparks, flames, or other sources of ignition. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Molybdenum disulphide	3 mg/m3 TWA (as Mo) Respirable fraction. 10 mg/m3 TWA (as Mo) Inhalable fraction.	15 mg/m3 TWA (as Mo) Total dust.	None	None
Propane/Isobutane	None	None	None	None
Acetone	500 ppm TWA 750 ppm STEL	1,000 ppm (2,400 mg/m3) TWA	None	None
n-Heptane	500 ppm STEL 400 ppm TWA	500 ppm (2,000 mg/m3) TWA	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) TWA	None	None
Calcium dihydroxide	5 mg/m3 TWA	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) TWA 5 mg/m3 TWA Mist.	None	None
Distillates (petroleum), hydrotreated light naphthenic	Exposure by all routes should be carefully controlled to levels as low as possible. Included in the regulation but with no data values. See regulation for further details	5 mg/m3 TWA mist 10 mg/m3 TWA mist 5 mg/m3 TWA Mist. 500 ppm (2,000 mg/m3) TWA	None	None

**Engineering controls:**

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

**Respiratory protection:**

When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed.

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Chemical resistant, impermeable gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Liquid

**Color:**

Black

Odor:	Solvent
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	< -17 °C (< 1.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	45 % (calculated)

## 10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Not available.
Hazardous decomposition products:	Oxides of carbon.
Incompatible materials:	Oxidizing agents.
Conditions to avoid:	Extremes of temperature and direct sunlight.

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Molybdenum disulphide	No	No	No
Propane/Isobutane	No	No	No
Acetone	No	No	No
n-Heptane	No	No	No
Methyl acetate	No	No	No
Calcium dihydroxide	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	Known To Be Human Carcinogen.	Group 1	No
Distillates (petroleum), hydrotreated light naphthenic	Known To Be Human Carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs
Molybdenum disulphide	No Target Organs
Propane/Isobutane	No Records
Acetone	Blood, Central nervous system, Irritant, Reproductive
n-Heptane	Central nervous system, Irritant
Methyl acetate	Blood, Central nervous system, Eyes, Irritant
Calcium dihydroxide	Irritant, Corrosive
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant
Distillates (petroleum), hydrotreated light naphthenic	Irritant

## 12. ECOLOGICAL INFORMATION

### Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** D001: Ignitable.

## 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Aerosols  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None  
**DOT Reportable quantity:** Acetone

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aerosols, flammable  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** AEROSOLS (n-Heptane)  
**Hazard class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** None  
**Marine pollutant:** n-Heptane

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12(b) Export Notification:** None above reporting de minimus  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Fire, Pressure, Immediate Health  
**CERCLA/SARA 313:** None above reporting de minimis  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.  
**WHMIS hazard class:** A, B.5, D.2.A, D.2.B

## 16. OTHER INFORMATION

**This material safety data sheet contains changes from the previous version in sections:** First issue.

**Prepared by:** Lou Fabrizio, Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.