# **Safety Data Sheet**



Revision Number: 002.0

Issue date: 05/07/2014

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type: Restriction of Use: Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE 680 RETAIN CMPND 0.5ML Adhesive None identified

IDH number: 1835212 Item number: 1835212 Region: **United States** Contact information: Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



**Precautionary Statements** 

Prevention:	Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face protection. Wear protective gloves.
Response:	F ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)         CAS Number         Percentage*	
---	--

Dimethacrylate ester	Proprietary	30 - 60
Methacrylate monomer	Proprietary	10 - 30
2-Hydroxyethyl methacrylate	868-77-9	10 - 30
Polyurethane methacrylate resin	Unknown	5 - 10
Acrylic acid	79-10-7	1 - 5
Hydroxyalkyl methacrylate	27813-02-1	1 - 5
Polyglycol dimethacrylate	Proprietary	0.1 - 1
Methacrylic acid	79-41-4	0.1 - 1
Cumene hydroperoxide	80-15-9	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.	
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get mediattention.	
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 1 minutes. Get medical attention.	
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.	
Symptoms:	See Section 11.	
5. FI	RE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear. In case of fire, keep containers cool with water spray.	
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.	
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.	

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. Refer to Section 8.

Storage:

For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Dimethacrylate ester	None	None	None	None
Methacrylate monomer	None	None	None	None
2-Hydroxyethyl methacrylate	None	None	None	3 ppm Ceiling
Polyurethane methacrylate resin	None	None	None	None
Acrylic acid	2 ppm TWA (SKIN)	None	None	1 ppm TWA 3 ppm STEL (SKIN)
Hydroxyalkyl methacrylate	None	None	None	1 ppm TWA 3 ppm STEL
Polyglycol dimethacrylate	None	None	None	None
Methacrylic acid	20 ppm TWA	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None

**Engineering controls:** 

**Respiratory protection:** 

Eye/face protection:

Skin protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use a NIOSH approved air-purifying respirator with an organic vapor cartridge. If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator must be used.

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Boeific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Green Characteristic Not available. Not available. Not available. Not available. 1.1 Not available. 93.3 °C (199.94 °F) Not available. Not available. Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Not available. Not available. Not available. Not available. 0.43 %; 4.74 g/l Not available. Not available.

# **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.
Incompatible materials:	Peroxides. Free radical initiators. Alkali metals
Reactivity:	Not available.
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

### **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye damage.
Ingestion:	May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Dimethacrylate ester	None	Irritant, Allergen	
Methacrylate monomer	None	No Records	
2-Hydroxyethyl methacrylate	Oral LD50 (RAT) = 11.2 g/kg Oral LD50 (RAT) = 5,050 mg/kg	Irritant, Allergen	
Polyurethane methacrylate resin	None	Irritant, Allergen	
Acrylic acid	Oral LD50 (RAT) = 33.5 mg/kg Oral LD50 (RAT) = 2.5 g/kg Oral LD50 (RAT) = 193 mg/kg Oral LD50 (RAT) = 1,250 mg/kg Inhalation LC50 (RAT, 4 h) = 1,200 mg/l	Allergen, Corrosive, Irritant, Kidney, Liver	
Hydroxyalkyl methacrylate	None	Irritant, Allergen	
Polyglycol dimethacrylate	None	Irritant, Allergen	
Methacrylic acid         Oral LD50 (RABBIT) = 1,200 mg/kg           Oral LD50 (RAT) = 1,060 mg/kg           Oral LD50 (RAT) = 2,224 mg/kg           Dermal LD50 (RABIT) = 500 mg/kg           Inhalation LC50 (RAT, 4 h) = 7.1 mg/l		Corrosive, Irritant, Allergen	
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Dimethacrylate ester	No	No	No
Methacrylate monomer	No	No	No
2-Hydroxyethyl methacrylate	No	No	No
Polyurethane methacrylate resin	No	No	No
Acrylic acid	No	No	No
Hydroxyalkyl methacrylate	No	No	No
Polyglycol dimethacrylate	No	No	No
Methacrylic acid	No	No	No
Cumene hydroperoxide	No	No	No

# **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

### **13. DISPOSAL CONSIDERATIONS** Information provided is for unused product only. Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Hazardous waste number: Not a RCRA hazardous waste. **14. TRANSPORT INFORMATION** The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration. U.S. Department of Transportation Ground (49 CFR) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None International Air Transportation (ICAO/IATA) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None Water Transportation (IMO/IMDG) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None **15. REGULATORY INFORMATION United States Regulatory Information** TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. TSCA 12 (b) Export Notification: None above reporting de minimis CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

# CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Acrylic acid (CAS# 79-10-7). CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg) California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Canada Regulatory Information Canada Regulatory Information

CEPA DSL/NDSL Status:

One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

# **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Sheila Gines, Regulatory Affairs Specialist

Issue date: 05/07/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.