SPECIFICATION SHEET : T1UNV024V-100LE 349510 RoHS COMPLIANT This Is An Original Product From Fulham Co., Inc


Description: 24V, 100W Constant Voltage LED Driver. Universal input range of 120-277V. One, 24V independent, constant voltage output channel.

This Driver Will Operate The Following LED Modules:

Any LED module designed to accept constant voltage input of 24V and has a maximum input current of 4.17A.

ELECTRICAL DATA

| | | 120 277 /// 60/ |
|--------------------------------|----|--|
| INPUT VOLTAGE | | 120-277VAC, 50/60Hz |
| INPUT CURRENT (MAX) | | 0.92A@ 120V, 0.41A@ 277V |
| POWER FACTOR (PF) | | >0.9 |
| тно | | <15% |
| EFFICIENCY | | >87% @ 120V FULL LOAD |
| DRIVE METHOD | | CONSTANT VOLTAGE |
| OUTPUT CURRENT | | 4.17A |
| OUTPUT VOLTAGE | | 24VDC |
| OUTPUT WATTAGE | | 100W |
| NUMBER OF OUTPUT CHANNELS | | 1 |
| RFI/EMI | 10 | FCC PART 15B CONSUMER |
| SOUND RATING | | A |
| CIRCUIT PROTECTION | | SURGE PROTECTION |
| | | CURRENT PROTECTION |
| | | OUTPUT SHORT CIRUIT PROTECTION |
| | | OUTPUT OPEN CIRCUITPROTECTION |
| | | OUTPUT TO GROUND SHORT PROTECTION |
| | | OVERLOAD PROTECTION |
| MAX. CASE HOT SPOT TEMPERATURE | | 90°C |
| AMBIENT TEMPERATUREN RANGE | | - 40°C TO 57°C |
| SERVICE LIFE | | 50,000 HOURS |
| APPROVALS/CLASS | | CURus CLASS 2, CE, RoHS, DRY OR DAMP LOCATIONS |
| SURGE PROTECTION | | line to line 2KV, line to earth 3KV |



Fulham extends a limited warranty only to the original purchaser or to the first user for a period of 5 years from the date of manufacture when properly installed and operated under normal conditions of use. For complete terms and conditions, please reference the Fulham product catalog (www.fulham.com) Due to a program of continuous improvement, Fulham reserves the right to make modifications or variations in design or construction to the equipment described. © Fulham Company Limited, All Rights Reserved.