

LIFTING CHAIN (S5)

316L STAINLESS STEEL



ITEM	SIZE	A	B	C	D	E	WLL	BL	WT
							(lb)	(lb)	(lb/ft)
S0603-0005*	3/16"	0.19"	0.58"	0.25"	0.66"	0.97"	1,100	4,400	0.36
S0603-0007	1/4" (9/32)	0.28"	0.85"	0.38"	0.97"	1.38"	2,200	8,800	0.67
S0603-0008	5/16"	0.32"	0.95"	0.45"	1.11"	1.55"	2,700	10,800	0.98
S0603-0010*	3/8"	0.39"	1.18"	0.55"	1.34"	1.96"	4,400	17,600	1.41
S0603-0013*	1/2"	0.51"	1.55"	0.75"	1.78"	2.53"	7,300	29,200	2.60

RATED FOR OVERHEAD LIFTING

NOTE: CALIBRATED SUNCOR GRADE 50 LIFTING CHAIN, MADE TO GRADE 80 DIMENSIONS. NEVER EXCEED WORKING LOAD LIMIT. WORKING LOADS ARE BASED ON GRADUAL PULL AND NOT SHOCK LOADS. MAKE SURE THAT ALL COMPONENTS IN YOUR ASSEMBLY ARE OVERHEAD LIFTING RATED AND HAVE THE SAME WORKING LOADS.

